Phone: +86-20-39390663 - Email: sales@lyintl.com

L-406TKS/L-506TKS/L-606TKS 4"/5"/6" Ceiling Speaker with ABS Cover and Power Taps

Product ID: L-406TKS/L-506TKS/L-606TKS



Short Description

Rated power: 20W/30W/40W Line input: 70V/100V/8?

Speaker driver: 4" or 5" or 6" PP woofer + 1" Mylar tweeter

Description

Elevate your public address and background music systems with these premium ceiling-mounted speakers.



Featuring a durable iron front grille and a high-strength ABS rear cover, these speakers are designed for lasting performance.



Available with 70V/100V and 8? inputs, they offer flexibility with a power taps switch.

Choose from 4", 5", or 6" PP cone woofers, paired with a 1" Mylar coaxial tweeter for outstanding audio quality.

Perfect for indoor use, these CE-certified speakers deliver superior sound and are ideal for any indoor environment.

Specification

| Model | L-406TKS | L-506TKS | L-606TKS |
|-------------|--------------|----------------|-------------|
| Rated power | 20W | 30W | 40W |
| Power taps | 2.5/5/10/20W | 3.8/7.5/15/30W | 5/10/20/40W |

| Line input | 70V/100V/8? | | | |
|---------------------|-------------------------|-----------|-------------|--|
| Sensitivity (1m,1W) | 87±3dB | 88±3dB | 90±3dB | |
| Frequency response | 90-20KHz | 80-20KHz | 70-20KHz | |
| Woofer speaker | 4" PP | 5" PP | 6" PP | |
| driver | | | | |
| Tweeter speaker | 1" Mylar | | | |
| driver | | | | |
| Product dimension | ?200x150 | ?230x150 | ?270x180 | |
| (mm) | | | | |
| Hole for mounting | ?180 | ?210 | ?250 | |
| (mm) | | | | |
| Frame material | ABS | | | |
| Grille material | Powder coated Iron mesh | | | |
| Color | White (RAL9016) | | | |
| Product net weight | 1.8 | 2 | 2.7 | |
| (Kg) | | | | |
| Gross weight | 17Kg/8pcs | 18Kg/8pcs | 13.4Kg/4pcs | |
| Packing dimension | 54x50x42 | 59x55x43 | 64x34x49 | |
| (cm) | | | | |

Product Gallery







