

# ED-120M/ED-240M/ED-360M/ED-480M/ED-600M 5 Zone Digital Mixer Amplifier with MP3 Record Player/Digital Tuner/Remote Paging

**Product ID:** ED-120M/ED-240M/ED-360M/ED-480M/ED-600M



## Short Description

Rated output power: 120W/240W/360W/480W/600W  
Combined with MP3 Record Player/Digital Tuner/Paging  
6 MIC input, 3 AUX input  
With remote paging MIC input

## Description

- ? Rated output power: 120W/240W/360W/480W/600W
- ? Combined with MP3 Record Player/Digital Tuner/Paging
- ? 6 MIC input (3 XLR), 3 AUX input, MIC1 with priority muting function, input individual volume control, treble & bass & master volume control
- ? 5 zone 100V speaker output, 1 zone 4/8? speaker out (ED-120M/ED-240M/ED-360M)
- ? 2 line amplifier input, 2 line amplifier out
- ? With remote paging MIC input (RJ45 interface)
- ? Telephone paging function (Euro block)

? Music on hold fuction (Euro block)

? Siren & Chime function

? LED indicators: Power, SIG, -20dB, -10dB, 0dB, CLIP & protect, zone selector

## Specification

| Model                     | ED-120M                                                                                                                                                                                                                                    | ED-240M                                       | ED-360M                                         | ED-480M     | ED-600M     |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|-------------------------------------------------|-------------|-------------|
| Rated output power        | 120W                                                                                                                                                                                                                                       | 240W                                          | 360W                                            | 480W        | 600W        |
| Output / Impedance        | 100V(83?)<br>70V(42?)<br>25V(5.2?)<br>22V(4?)                                                                                                                                                                                              | 100V(42?)<br>70V(21?)<br>25V(2.6?)<br>31V(4?) | 100V(28?)<br>70V(13.6?)<br>25V(1.7?)<br>38V(4?) | 100V(20.8?) | 100V(16.7?) |
| Audio play output         | 0dB / 600? balanced                                                                                                                                                                                                                        |                                               |                                                 |             |             |
| Pre-amplifier output      | 0dB / 600? unbalanced                                                                                                                                                                                                                      |                                               |                                                 |             |             |
| Input sensitivity         | Channel 1-3, MIC: -54dB to -6dB Variable / 20K? balanced<br>Channel 4-6, Line: -30dB to +14dB Variable / 20K? balanced<br>Remote paging, MIC: 0dB / 20K? balanced<br>Tel-paging: -17dB / 600? balanced<br>Amp/line in: 0dB/10K? unbalanced |                                               |                                                 |             |             |
| Frequency response        | 80Hz-18KHz                                                                                                                                                                                                                                 |                                               |                                                 |             |             |
| T.H.D.                    | <0.1%                                                                                                                                                                                                                                      |                                               |                                                 |             |             |
| S/N ratio                 | >80dB                                                                                                                                                                                                                                      |                                               |                                                 |             |             |
| Graptic source (±12dB)    | 125Hz, 250Hz, 500Hz, 1KHz, 2KHz, 4KHz, 8KHz                                                                                                                                                                                                |                                               |                                                 |             |             |
| Power supply              | AC230V, 50/60Hz                                                                                                                                                                                                                            |                                               |                                                 |             |             |
| Protection                | Overheat, overload                                                                                                                                                                                                                         |                                               |                                                 |             |             |
| Net weight                | 6.3Kg                                                                                                                                                                                                                                      | 7.3Kg                                         | 8.3Kg                                           | 5.5Kg       | 5.5Kg       |
| Product dimension (WxDxH) | 420x320x88mm                                                                                                                                                                                                                               |                                               |                                                 |             |             |

## Product Gallery

