

DA-4060/DA-4125/DA-4250 4 Channel Class D Digital Amplifier

Product ID: DA-4060/DA-4125/DA-4250



Short Description

Rated output power: 4*60W / 4*125W / 4*250W
70V/100V power output
1 U slim design

Description

- ? Multiple channels in 19” standard rack cabinet
- ? 70V/100V power output optional
- ? Full digital with 4*60W / 4*125W / 4*250W high efficiency
- ? With priority input function and 100V input
- ? 1 U slim design, space and cost saving
- ? With standby function for power saving

Specification

Model	DA-4060	DA-4125	DA-4250
-------	---------	---------	---------

Channel	4		
Rated power per channel	60W	125W	250W
Rated output power	70V/100V		
Input sensitivity	775mVRMS(0dBV/balanced input) 100VRMS (100V unbalanced input)		
S/N ratio	>80dB		
Input impedance	60K Ohms (balanced) 20K Ohms (priority) 100K Ohms (100V unbalanced)		
Frequency response	80Hz-15kHz (± 3 dB)		
T.H.D.	<0.3% (1kHz)		
Power consumption	300W	600W	1200W
Power requirement	AC180-260V/50-60Hz DC24V(rated power -3dB)		
Net weight (Kg)	7.4	7.7	8.0
Gross weight (Kg)	8.8	9.0	9.3

Product Gallery

