

L-511T/L-611T/L-811T 5"/6"/8" Ceiling Speaker with 1/2" Mylar Tweeter

Product ID: L-511T/L-611T/L-811T



Short Description

Rated power: 20W/30W/40W

Line input: 100V

Woofer speaker driver: 5"/6"/8" PP, 1/2" Mylar tweeter

Description

ABS ceiling speaker with 5"/6"/8" PP woofer speaker driver and 1/2" Mylar tweeter, 100V transformer.

Specification

Model	L-511T	L-611T	L-811T
Rated power	20W	30W	40W
Power taps	5/10/20W	7.5/15/30W	10/20/40W
Line input voltage	100V		
Sensitivity (1m,1W)	88±3dB		
Frequency response	100-20KHz	90-20KHz	50-20KHz
S.P.L.	100dB at 100V/10W	102dB at 100V/15W	103dB at 100V/20W
Woofer speaker driver	5" PP (foam edge)	6" PP (foam edge)	8" PP (foam edge)

Tweeter speaker driver	1/2" Mylar		
Product dimension (mm)	φ203x80	φ230x90	φ270x105
Hole for mounting (mm)	φ170	φ200	φ240
Frame material	ABS		
Grille material	Powder coated Iron mesh		
Color	White (RAL9016)		
Product net weight (Kg)	1.2	1.4	2
Gross weight	13Kg/8pcs	14.5Kg/8pcs	16Kg/6pcs
Packing dimension (cm)	50x44x29	54x47x31	61x42x35

Product Gallery



