

PB-2011P Pre Amplifier

Product ID: PB-2011P



Short Description

5 MIC/3 AUX inputs, 2 priority inputs

4 AUX outputs

Individual volume control for MIC & AUX

Description

? 5 MIC inputs, 3 AUX inputs, 2 priority inputs (EMC)

? MIC1 overrides MIC2-5 & AUX1-3

? 4 AUX outputs

? Individual volume control for EMC & AUX inputs

? EMC1 & 2 overrides all other inputs except MIC1

? Build-in chime music

? LED power indicator

Specification

Model	PB-2011P
Inputs	Mic1, 2, 3, 4, 5: 600 Ω , 18mV, unbalanced
	Aux1, 2, 3 : 10K Ω , 200mV, unbalanced

	EMC1, 2: 10K Ω , 1.5V, unbalanced
S/N	MIC1, 2: 70dB
	AUX 1, 2, 3: 80dB
Frequency Response	20Hz-20KHz
Tone	Bass : ± 10 dB(100Hz)
	Treble : ± 10 dB (10KHz)
T.H.D.	<0.1%
Muting Function	MIC1 overrides other input with 0-30 dB attenuation; EMC1, 2 overrides all inputs except MIC1
Protection	AC fuse
Power Requirements	AC 110V / 220V($\pm 10\%$), 50 / 60 Hz
Power Consumption	50W
Net Weight (Kg)	7.5
Product Dimensions (mm)	483(W) x 366(D) x 89(H)

Product Gallery

