

# M-808R 8 Zone Remote Paging Microphone

**Product ID: M-808R**



## Short Description

Support 8 zone paging  
Built-in 2 chime signal  
MIC and chime volume adjustable

## Description

M-808R is a remote paging MIC equipped for M-808 Digital Audio Matrix Public Address System. It's a functional remote paging MIC, each MIC can control 8 zones, each zone can realize independent control or one key switch and it support multi-level extension.

- ? Support 8 zone paging
- ? Signal level LED indicator
- ? Built-in 2 chime signal
- ? MIC and chime volume adjustable
- ? Adopts D626 goose-neck microphone
- ? Adopts RJ45 interface for MIC connection

Specification

Model		M-808R
Input sensitivity	MIC	45±5 mV
	Net prot (balanced)	2000±100 mV
Net port output voltage (Balance)		2000±100 mV
Chime rated output level		?1000 mV
Output control signal type		RS485 + Analog audio signal?net port? 10P computer extension socket and priority dial
MIC frequency response		100Hz?15kHz (±3dB)
Noise		<1.5mV
Distortion		<0.5% at 1KHz
Power supply		~220V/50Hz
Product size (L×W×H) mm		231.5×145.5×67.5
Packing size (L×W×H) mm		282×200×264 (1pc)
Net weight (Kg)		1.75
Gross weight (Kg)		2.0 (1pc)

Product Gallery

