

M-6401 2x25W Network Terminal Player

Product ID: M-6401



Short Description

Build-in 2x25W digital amplifier
1 AUX input, 1 MIC input, 1 AUX output
Support offline local source playing

Description

M-6401 is a terminal in Network Public Address systems. Fully digital design with hi-fi and high speech transmission index.

- ? All digital design, high fidelity audio transmission
- ? Build-in local off-line program timing play function, timing programs backup in SD card, automatically timing play
- ? Digital display, can display time or playing process
- ? Can connect to M-6402 broadcast control panel, achieve playing main unit programs freely
- ? With USB input, USB audio programs can be timing played
- ? Two network backup design, automatically LAN problem detect and network switch
- ? EMC 24V and short circuit output port
- ? Build-in 2x25W digital amplifier
- ? 1 AUX input, 1 MIC input, 1 AUX output
- ? Local MIC input with mute function
- ? 4 LED indicate machine working status

? 8 push buttons for daily normal operation

Specification

Model	M-6401	
AUX Input / Output	Sensitivity	1000mV
	Frequency response	20Hz-20KHz
	T.H.D	?0.1%
	S/N	?75dB
MIC Input	Sensitivity	10mV
	Frequency response	20Hz-20KHz
	T.H.D	?0.5%
	S/N	?70dB
MAX output power	2x25W / 4?	
	1x50W / 8?	
Control mode	Manual control, remote control	
Line output level	1V-1.2V	
Power supply	AC 150V-250V/50-60Hz	
Dimension (mm)	(L×W×H) 220×195×50	
Packing dimension (mm)	(L×W×H) 330×270×125	
Net weight (Kg)	1.3	

Product Gallery



M-6401 Connection Diagram

