

M-6801/M-6804 1 or 4 Channel Network Audio Output Terminal

Product ID: M-6801/M-6804



Short Description

Dual network interface

1 or 4 CH audio signal output

Can play any audio signal from host

Description

Two network connection ports, can work between different networks; Can play background music, emergency paging and alarm signal from the host; One EMC input, one EMC output.

- ? All-digital design, high fidelity and high speech transmission
- ? 1 channel / 4 channel audio signal output simultaneously
- ? Dual network interface, can expand to other network equipments
- ? DC 24V/100MA output and short circuit output, two output mode are controlled simultaneously
- ? 10M/100M self-adaptive network transmission
- ? Support the maximum 48KHZ, sampling rate 16Bit MP3/ WAV/PCM decoding
- ? Built-in watchdog function
- ? Customize network protocol interface
- ? Combined with forced plug input and linked output

? Local monitoring volume is controllable

Specification

| Item | | | Parameter |
|--|--|------------------------------------|---|
| EMC parameters (EMC LINE IN port input) | M-6801 | CH1 rated output | 1V |
| | M-6804 | CH1, CH2, CH3 and CH4 rated output | 1V |
| | Input sensitivity | MAX | 250mV |
| | | MIN | 4V |
| | Effective frequency range of gain limit (±3dB) | | 50Hz-20kHz |
| | Signal-noise ratio (low pass 30kHz) | | ≥70dB |
| | T.H.D. (1kHz, 1/3 output voltage) | | ≤0.1% |
| | EMC LINK output | | Equal to EMC LINE input (±10%) |
| | Input dynamic scope | | ≥26dB |
| Network decoding parameters (host machine MP3 input) | M-6801 | CH1 | 1V |
| | M-6804 | CH1, CH2, CH3 and CH4 rated output | 1V |
| | Distortion degree (1kHz -10dB/MP3) | | ≤0.2% |
| | Effective frequency range of gain limit (±3dB) | | 50Hz-20kHz |
| | Signal-noise ratio (low pass 30kHz) | | ≥70dB |
| Alarm output (Host software control) | COM-24V output | | 24V (≤100mA) |
| | COM-SC output | | Short circuit (≤1?) |
| Built-in monitoring power | | | 1.2W |
| Network | | | Dual network interface 10M/100M self-adaptive |
| Power supply | | | AC 180V-242V/50Hz |
| Power consumption | | | 12W |
| Product dimension (LxWxH mm) | | | 555x360x120 |
| Packing dimension (LxWxH mm) | | | 482x273x44 |
| Net weight (Kg) | | | 3.31 |

Product Gallery

