

M-6463 25W IP Network Wall Mount Speaker

Product ID: M-6463



Short Description

Built-in 2x25W digital amplifier

Built-in 4? 25W Hi-Fi speakers

1 AUX & 1 MIC input, 1 AUX output

Description

Support infrared remote control and easy to connect with the local fire alarming system.
Built in Hi-Fi speaker for clear and sonorous sound.

- ? 100/10Mbps, TCP/IP network transmission protocol adaptive
- ? High class waterproof grille, engineering plastic mold design
- ? Built-in 2x25W high efficiency digital amplifier with low power-consuming
- ? Built-in 25W 4? Hi-Fi speakers with high output sensitivity
- ? 1 auxiliary audio input, 1 microphone input, 1 auxiliary audio output
- ? 100V local emergency input, easy to connect with the local fire alarming system
- ? Accept infrared remote control

Specification

Model		M-6463
AUX Input	Input impedance	>10k?
	Input sensitivity	1000mV

	Frequency response	50Hz-20kHz
	Distortion	≤0.1%
	S/N	≥80dB
MIC Input	Input impedance	>600Ω
	Frequency response	50Hz-20kHz
	Distortion	≤0.1%
	S/N	≥75dB
AUX Output	Output impedance	<50Ω
	Output sensitivity	1000mV
	Frequency response	50Hz-20kHz
	Distortion	≤0.1%
	S/N	≥75dB
Amplifier Output	Power	25W/4Ω
	Frequency response	50Hz-20kHz
	Distortion	≤0.1%
	S/N	≥80dB
Built-in Speaker	Max SPL	≥100dB
	Power	25W/4Ω
	Frequency response	50Hz-20kHz
	Distortion	≤0.1%
	S/N	≥80dB
Interface	Dual ethernet interface	CAT-5
	AUX input	RCA
	AUX output	RCA
	MIC input	6.3 Socket
	AUX speaker output	3.81mm
Digital Audio Parameter	Decode format	Support PCM\MP3
	Sampling frequency	8k-48kHz
Other	Power supply	180-250V/50Hz
	Over-current	Yes
	Over-heat Over-voltage Protection	

Product Gallery

