

# M-6311 15W IP Network Ceiling Speaker

**Product ID:** M-6311



## Short Description

Built-in 2x15W digital amplifier  
Built-in 4? 15W Hi-Fi speakers  
1 AUX & 1 MIC input, 1 AUX output

## Description

Support BGM, emergency paging and siren alarm from the system center host machine;  
Local MP3 program can be played when the network audio stream signal is not played;  
1 AUX audio input for connection with other audio source devices (such as DVD);  
1 AUX audio output for connection with other power amplifiers;  
1 MIC input for achieving local paging.

- ? 100/10Mbps, TCP/IP network transmission protocol adaptive
- ? Built-in 2x15W high efficiency digital amplifier with low power-consuming
- ? Built-in 15W 4? Hi-Fi speakers with high output sensitivity
- ? 1 AUX audio input, 1 microphone input, 1 AUX audio output
- ? 100V local emergency input, easy to connect with the local fire alarming system
- ? Output volume and display status can be controlled by system host

## Specification

Model	M-6311
-------	--------

AUX Input	Input sensitivity	1000mV
	Frequency response	20Hz-20kHz
	Distortion	≤0.5%
	S/N	≥75dB
MIC Input	Output sensitivity	10mV
	Frequency response	20Hz-20kHz
	Distortion	≤0.5%
	S/N	≥65dB
AUX Output	Rated output	1000mV
	Frequency response	20Hz-20kHz
	Distortion	≤0.3%
	S/N	≥75dB
Amplifier Output	Power	15W/4Ω
	Frequency response	20Hz-20kHz
	Distortion	≤0.5%
	S/N	≥75dB
Built-in Speaker	Max SPL	≥100dB
	Power	15W/4Ω
	Frequency response	20Hz-20kHz
	Distortion	≤0.5%
	S/N	≥75dB
USB/SD/Net/MP3	Frequency responses	20Hz-20kHz
	Distortion	≤0.5%
	S/N	≥70dB
SD card storage		32GB
U disk storage		32GB
Power Supply		180-250V/50-60Hz
Product weight (Kg)		1.5
Dimension (LxWxH mm)		250x175x255