

M-6463POE 10W POE IP Network Wall Mount Speaker

Product ID: M-6463POE

Short Description

POE supportable speaker
Built-in 2x10W digital amplifier
Built-in 4? 10W Hi-Fi speakers

Description

POE supportable wall mount speaker;

Built in Hi-Fi speaker for clear and sonorous sound;

Support any audio sources play from the system center host machine, and local MP3 audio decoding.

? 100/10Mbps, TCP/IP network transmission protocol adaptive

? High class waterproof grille, engineering plastic mold design

? Built-in 2x10W high efficiency digital amplifier with low power-consuming

? Built-in 15W 4? Hi-Fi speakers with high output sensitivity

Specification

Model		M-6463POE
AUX Input	Input impedance	>10k?
	Input sensitivity	1000mV
	Frequency response	50Hz-20kHz
	Distortion	?0.1%
	S/N	?80dB
MIC Input	Input impedance	>600?
	Frequency response	50Hz-20kHz
	Distortion	?0.1%
	S/N	?75dB
AUX Output	Output impedance	<50?
	Output sensitivity	1000mV
	Frequency response	50Hz-20kHz
	Distortion	?0.1%

	S/N	≥75dB
Amplifier Output	Power	10W/4Ω
	Frequency response	50Hz-20kHz
	Distortion	≤0.1%
	S/N	≥80dB
Built-in Speaker	Max SPL	≥100dB
	Power	10W/4Ω
	Frequency response	50Hz-20kHz
	Distortion	≤0.1%
	S/N	≥80dB
Interface	Dual ethernet interface	CAT-5
	AUX input	RCA
	AUX output	RCA
	MIC input	6.3 Socket
	AUX speaker output	3.81mm
Digital Audio Parameter	Decode format	Support PCM\MP3
	Sampling frequency	8k-48kHz
Power supply		48V POE, IEEE802.3at standard
Over-current, over-heat, over-voltage Protection		Yes
Packing dimension (LxWxH mm)		590x275x390
Product dimension (LxWxH mm)		310x215x150
Net weight (Kg)		4.2

Product Gallery

