

L-VBM20A/EN Honeywell 20W Aluminum Bidirectional Projection Loudspeaker

Product ID: L-VBM20A/EN



Short Description

Rated power: 20W (10Wx2)

Meets outdoor requirements

EN54-24 certified, IP65 standard

Description

L-VBM20A/EN is a high-performance 20W voice alarm bidirectional projection loudspeaker. It provides a broad frequency response range, low distortion and high sound pressure level for accurate and intelligible broadcast of evacuation messages and high-quality sound reproduction. It can be used in indoor, outdoor, dry, or wet applications, providing

reliable operations over wide temperature and humidity ranges. Bidirectional loudspeaker is the best choice for applications such as tunnel, gallery and shopping arcade. This voice alarm bidirectional projection loudspeaker complies with BS 5859 part 8 and EN54 part 24.

- ? Intelligible voice and superior sound reproduction
- ? Ceiling or wall mount
- ? Meet virtually any outdoor requirements

- ? EN54-24 certified
- ? Complies with IP65 standard
- ? Available with or without capacitor (part number without “C”)

Specification

Model	L-VBM20A/EN (C)	L-VBM20A/EN
Max power	30W	
Rated power	20W (10Wx 2)	
Power taps @ 100V	20W / 10W / 5W / 2.5W	
SPL at 20W / 1W (100 Hz-10 KHz,1m)	99dB / 87dB	
SPL at 20W / 1W (100 Hz-10 KHz,4m)	87dB / 75dB	
Frequency response(-10dB)	150 Hz - 20 KHz	
Rated input voltage	100 V / 70 V	
Rated impedance	500 ? / 1K ? / 2K ? / 4K ?	
Connection	Fire-resistant Cable	
Dimensions (D x L)	?140 mm x195 mm	
Weight	3.23 Kg	
Color	White (RAL9003)	
Material	Aluminum	
DC Blocking Capacitor	Yes (2.7uF)	No

Product Gallery

