

# M-9102 32 Channel IP Network Fire Alarm Terminal

**Product ID:** M-9102



## Short Description

32 CH fire alarm input

Support short circuit & 5V-24V signal

Based on TCP/IP protocol

## Description

Used for collecting occasion's monitoring, smoke detection and emergency signals.

When alarm signal is received, the IP Network Fire Alarm Terminal will send the signal to the server for forced insertion of the emergency broadcast sound.

? Based on TCP/IP protocol

? 32 Channel fire alarm signal input, 32-way independent control, support adjacent zone alarm

? Support short circuit and 5V-24V signal

? Alarm sound signal can be customized via management software

? 10 / 100M adaptive, support DHCP/static IP, support LAN and WAN

? Control area can be extended by connecting more pieces of this device to the network

? 1 U slim small size design

### Specification

| Item                 | Specification                       |
|----------------------|-------------------------------------|
| Channels supported   | 32                                  |
| Way of display       | LED                                 |
| Protocol supported   | TCP/IP, UDP, ICMP, IGMP (Multicast) |
| Activate neighbor    | Multiple, programmable              |
| Trigger signal level | 5V-24V                              |
| Protection           | AC fuse×1                           |
| Input mode           | Short circuit, 12V~24V              |
| Power input          | ~220V/50Hz                          |
| Network              | RJ45 (10/100M)                      |
| Size (mm)            | 44×430×213 (H×W×D)                  |
| Net weight (Kg)      | 2.3                                 |