

M-9151/M-9152/M-9153/M-9154 IP Network Amplifier

Product ID: M-9151/M-9152/M-9153/M-9154



Short Description

RMS: 60W/120W/250W/500W

Class-D digital amplifier

Based on TCP/IP protocol

Description

This series IP network digital amplifier can work off-line independently from the network.

? Rated power (RMS): 60W/120W/250W/500W, 100V output

? Class-D digital amplifier based on TCP/IP protocol

? High-level protection circuit, output short circuit protection, overload protection, overheating protection and other protection and warning functions

? Built-in high efficiency digital amplifier, up to 90% efficiency

? Can be separated from the network and host, independent working operation

? Built-in mass storage, built-in program source,

? With timer function

? 1 U slim & compact design

Specification

Item	Specification			
Rated Power	M-9151	M-9152	M-9153	M-9154
	60W	120W	250W	350W
Speaker Output	70V/100V			
Input sensitivity	0dbV			
SNR	>80db			
Frequency signal	20HZ-20KHZ			
Harmonic distortion	?0.3%			
Protection	Limit, clip, signal, 70V			
Network	RJ45(10/100M)			
Network support protocol	DHCP, TCP/IP, UDP, ICMP, IGMP (Multicast), 802.1x, HTTP, HTTPS, FTP, DNS, DDNS, RFC3261, RTP, RTSP, RTCP, UPNP			
Power supply	~220V/50Hz			
Dimensions (mm)	44×430×213 (H×W×D)			
Product weight (Kg)	2.8			

Product Gallery

