

M-2588 250 Zone Remote Paging Station

Product ID: M-2588



Short Description

250 zones remote paging
1 AUX input and 1 AUX output
Host partition paging

Description

M-2588 series of remote paging selector adopts signal all-digital transmission design, high stability and low failure rate.

- ? 7 inch true color LCD touch screen, high-grade aluminum alloy panel design
- ? Desktop design
- ? High-fidelity and hand-held dynamic microphone design
- ? Possess multi-level indication, sound pressure is more intuitive
- ? Convenience quick paging in emergencies with manual shortcut keys
- ? 1 line audio input (connect the player devices such as a DVD player, tuner, wireless

microphone, etc.)

? 1 line audio output (connect to amplifier)

? Built-in bell sound

? Host partition paging function

Specificaition

Item	Parameter
Input sensitivity	Mic: 10mV(±1mV), unbalance Line: 300mV(±50mV), unbalance
Audio signal output	Line output: 1V?±0.1V?
	Chime output: 0.8V-1V
Chime output type	CHIME1: note1-3-5-i
	CHIME2: notei-5-3-1
	CHIME3: note i-5-i-5
Frequency response	Mic: 150Hz-10kHz(±3dB) Line: 20Hz-20kHz(±3dB)
Distortion	MIC: ?1.5%
	Line: ?0.1%
Signal to noise ratio	Mic input ?60dB Line input?70dB
Protection	AC fuseF1L
Power	AC 220-240V/50-60Hz/5W
Device size (mm)	(L×W×H) 270×180×120
Gross weight (Kg)	3.5
Net weight (Kg)	2.2

Product Gallery

