

H-8700C/H-8700D Infrared Wireless Conference System Microphone

Product ID: H-8700C/H-8700D



Short Description

OLED display microphone status
5 function keys setting function
Chairman unit priority function

Description

- ? Portable table moving and microphone pipe can be pull out. Extended pipe option
- ? Electric capacity type microphone, equipped with windshield cover
- ? OLED display microphone ID, signal level, battery level, microphone state, control channel, etc.
- ? Equipped with microphone on/off key and indicator
- ? Equipped with 5 function keys to support microphone ID/LCD contrast/Language setting and service calling function
- ? Microphone will shut off the power in 60 seconds to save battery power if system communication is error
- ? OLED will display "IR Signal Weak/Error" if ther IR signal is weak when microphone working

Including the functions of the delegate unit, chairman unit has other following functions:

- ? Chairman microphone can turn on any time
- ? In one system microphone just support one chairmann microphone and the ID number should be 1
- ? Priority function: chairman can turn off delegate microphone any time
- ? Chairman only mode: Delegate microphone can not be turned on again after chairman microphone press priority button. The chairman need quit this mode first, and then delegate microphone can be turned on again.

Specification

Item	Parameter
Transmission Method	Wireless infrared
Channels	4 audio + 1 data
Carrier Frequency Band	4MHz-8MHz
Modulation Method	FM/FSK
Infrared Radiator Consumption	+10dBm
Receiving Sensitivity	-100dbm
Mic Sensitivity	-44dB±2dB
Frequency Response	100Hz-12KHz
S/N Ratio	>82dB
T.H.D.	<0.5%
Reference Speaking Distance	10~30cm
Consumption Rating	8W
Operating Temperature Range	0-40 degree
Dimension (LxWxH) (mm)	168x145x60
Length of gooseneck (mm)	420 (optional)
Net Weight	1.2Kg (with battery)
Battery	LIP battery 12V/4000MAH

Product Gallery

