

H-7300 Full Function Digital Conference System

Product ID: H-7300



Short Description

Support discuss, video camera auto-track & voting

Support up to 250 units microphone with power extension unit

Description

? Designed accordance to ISO and IEC914 standards

? Main unit can support 60 units delegate and chairman microphone, it could be extend to support 250 units microphone with extension power unit

? Equipped with four groups of 8P-DIN interface for system connecting

? With the port for telephone interface input, telephone meeting is available with telephone coincidence

? Built-in monitor loudspeaker

? Main unit has following features when work without computer

1) LCD display the working mode on the front panel

2) Support many conference work mode: free, FIFO(1-9 microphone unit), limit(1-9 microphone unit)

? Main unit has following features when work with computer and other devices:

- 1) Manage the meeting with software, support double screen display
- 2) Voting function (yes,no abstain)
- 3) Electing function (single-ballot and multiple-ballot)
- 4) Audience response (100, 75, 50, 25, 0)
- 5) Video camera auto-track function
- 6) System can support discuss model: free mode, FIFO mode(1-9 microphone unit), Limit mode (1-9 microphone unit)

? Connection:

- 1) 1 pcs 13m main cable with 8 PIN plugs
- 2) 8 PIN socket for system connection

Specification

Item	Parameter
Power Supply	AC110V/240V 50Hz/60Hz
Consumption Rating	450W
T.H.D.	<0.05%
S/N	>75dB
Frequency Response	100Hz-18KHz
Color	Black
Net Weight	11.5Kg
Audio Input	RCAx1, ?6.35x1
Audio Output	RCAx2, XLRx1
Output Impedance	47K?
Video Input	8
Video Output	2
Control Type	RS-232
System Connection	8-PIN DINx4
Dimension (mm)	480x360x85
Installation	2U rack 19 inch frame

Product Gallery

