Phone: +86-20-39390663 - Email: sales@lyintl.com

Product ID: H-840B

H-840B UHF Wireless Meeting Microphone



Short Description

Frequency range: 470-960MHz

1 receiver & 4 transmitter

Description

- ? System include 1 receiver and 4 transmitter microphone
- ? Adopt UHF 470-960MHz PLL frequency synthesizer technology
- ? Adopt multi-channel high band and intermediate band frequency selective filtering, fully eliminate interference signal
- ? Build-in feedback eliminating technology which can decrease the feedback and noise effectively
- ? Build-in multiple noise detecting circuit and TONE-LOCK system to make sure the system has strong anti-jamming function
- ? Perfect performance with the best chips and components; adopt SMD original mount design to enhance the product quality and stability
- ? Operation distance up to 60 meters with the best condition, 40 meters in normal

condition

? Frequency and channel are locked to protect anti-jamming function

Specification

Model	H-840B
Carrier Frequency Range	UHF 470MHz~960MHz
Modulation	FM
Frequency Stability	200ppm
Frequency Response	60Hz~16KHz
Max deviation	±25KHz
T.H.D	<1%
RF output	30mW
Current consumption	100mA
Pressure limit sensitivity	-70 ~ -98dBM
Pilot carrier frequency	32KHz
Service Range	60M