

H-G08/2 8 Channel Professional Mixing Console

Product ID: H-G08/2



Short Description

4 CH Mono & 4 CH Mic input
2 channel stereo input
Rackmount installation design

Description

Using preamplifier as the main part, it can receive multi-channel audio signals of different impedances and levels and can equalize, mix, distribute these signals.

As long as you achieve the best SNR and timbre through adjustment, the pro mixing console will complete efficient and quality transmission of audio signals.

? 4 channels Mono and 4 channels MIC input, 2 channel stereo input

? High-performance microphone pre-amplifiers with switchable phantom power

? 3-band channel EQ and high-pass filters

? Build-in channel compressors

? Smooth 60-millimeter faders & Illuminated channel on switches

? Bright meters for visual level monitoring

Specification

Model	H-G08/2
Max output level	19dBm(1Hz, THD=0.5%)
Phones output	40mW(1Hz, THD=0.5%, 200?)
Input type	XLRx4, RCAx4
Frequency response	20Hz-20KHz
Residual noise SNR	-75dB
S/N	71dB
T.H.D.	?0.05% (1KHz, 0.775V)
EQ	LOW: 80Hz±15dB
	MID: 2.5KHz±15dB
	HIGH: 12KHz±15dB
Gain control	Mono: -55dB~0dB
	Sereo: -10dB~0dB
Power supply	AC220V 50~60Hz
Power consumption	25W
Dimension (LxWxH) (mm)	400x400x45
Net weight (Kg)	4.41

Product Gallery

