

L-518T/L-618T/L-818T 5"/6"/8" In Wall/Ceiling Mount Speaker with 1/2" Mylar Tweeter

Product ID: L-518T/L-618T/L-818T



Short Description

Rated power: 20W/30W/40W

Line input: 100V

Speaker driver size: 5" or 6" or 8" PP + 1/2" Mylar

Description

ABS in ceiling/wall mount speaker built-in 5" (L-518T), 6" (L-618T) or 8" (L-818T) PP cone speaker driver and 1/2" mylar tweeter, 100V transformer.

Power taps:

L-518T: 5/10/20W

L-618T: 7.5/15/30W

L-818T: 10/20/40W

Specification

Model	L-518T	L-618T	L-818T
Rated power	20W	30W	40W
Power taps	5/10/20W	7.5/15/30W	10/20/40W
Line input voltage	100V		

Sensitivity (1m,1W)	89±3dB		87±3dB
Frequency response	90-18KHz	90-20KHz	50-18KHz
Woofer speaker driver	5" PP	6" PP	8" PP
Tweeter driver	½" Mylar		
Product dimension (mm)	190x190x80	220x220x95	255x255x100
Hole for mounting (mm)	145x145	190x190	225x225
Frame material	ABS		
Grille material	Powder coated Iron mesh		
Color	White (RAL9016)		
Product net weight (Kg)	1.3	1.7	2.2
Gross weight	13.5Kg/8pcs	17Kg/8pcs	16Kg/6pcs
Packing dimension (cm)	50x44x29	54x47x31	61x42x35

Product Gallery



L-618T



L-418T