

H-P200/H-P350/H-P450/H-P650 Dual Channel Professional Amplifier

Product ID: H-P200/H-P350/H-P450/H-P650



Short Description

2-channel, parallel or bridged
2*200W (8?), 2*350W (8?)
2*450W (8?), 2*650W (8?)

Description

- ? 2-channel, parallel or bridged, mono operating modes for flexible application
- ? Independent limiters for each channel offer dependable protection against distortion
- ? Precise signal and clip LED indicators to monitor performance
- ? High-current toroidal transformer for absolute reliability and lowest noise emission
- ? Independent DC and thermal overheat protection on each channel automatically protects amplifier and speakers
- ? "Back-to front" ventilation system including air filler will automatically adjust fan speed for smooth operation

? Balanced XLR and 1/4? TRS inputs

? Professional connectors compatible to Speaker and "touch-proof" binding post
loudspeaker outputs enable secure operation

Specification

Model		H-P200	H-P350	H-P450	H-P650
Power supply		AC 220V 50~60Hz			
Input sensitivity/Impedance		500mV/20K ?	500mV/20K ?	500mV/22K ?	500mV/20K ?
Output power	8?	2x200W	2x350W	2x450W	2x650W
	4?	2x350W	2x550W	2x650W	2x850W
	Bridge 8?	600W	850W	1050W	1550W
Frequency response		20Hz-20KHz			
S/N		>90dB			
T.H.D.		<0.05%			
Channel cross-talk		<-70dB			
Channel impedance		4~16?			
Net weight (Kg)		12	13	14	19
Produce dimension (LxWxH) mm		430x430x125			
Color		Black			

Product Gallery

