

H-P300/H-P400 Dual Channel Professional Amplifier

Product ID: H-P300/H-P400



Short Description

2-channel, parallel or bridged

2*300W (8?)

2*400W (8?)

Description

? 2-channel, parallel or bridged, mono operating modes for flexible application

? Independent limiters for each channel offer dependable protection against distortion

? Precise signal and clip LED indicators to monitor performance

? High-current toroidal transformer for absolute reliability and lowest noise emission

? Independent DC and thermal overheat protection on each channel automatically protects amplifier and speakers

? "Back-to front" ventilation system including air filler will automatically adjust fan speed for smooth operation

? Balanced XLR and 1/4? TRS inputs

? Professional connectors compatible to Speaker and "touch-proof" binding post
loudspeaker outputs enable secure operation

Specification

Model		H-P300	H-P400
Power supply		AC 220V 50~60Hz	
Input sensitivity/Impedance		500mV/20K?	500mV/22K?
Output	8?	2x300W	2x400W
	4?	2x500W	2x600W
	Bridge 8?	800W	900W
Frequency response		20Hz-20KHz	
S/N		>90dB	
T.H.D.		<0.05%	
Channel crosstalk		<-70dB	
Channel impedance		4~16?	
Net weight (Kg)		14.2	15.8
Produce dimension (LxWxH)mm		430x430x125	
Color		Black	

Product Gallery

