

# H-P600 Dual Channel Professional Amplifier

**Product ID:** H-P600



## Short Description

2-channel, parallel or bridged

Output power: 2\*600W (8?)

## Description

? 2-channel, parallel or bridged, mono operating modes for flexible application

? Independent limiters for each channel offer dependable protection against distortion

? Precise signal and clip LED indicators to monitor performance

? High-current toroidal transformer for absolute reliability and lowest noise emission

? Independent DC and thermal overheat protection on each channel automatically protects amplifier and speakers

? "Back-to front" ventilation system including air filler will automatically adjust fan speed for smooth operation

? Balanced XLR and 1/4" TRS inputs

? Professional connectors compatible to Speaker and "touch-proof" binding post

loudspeaker outputs enable secure operation

## Specification

Model		H-P600
Power supply		AC 220V 50~60Hz
Input sensitivity/Impedance		500mV/20K?
Output power	8?	2x600W
	4?	2x800W
	Bridge 8?	1500W
Frequency response		20Hz-20KHz
S/N		>90dB
T.H.D.		<0.05%
Channel cross-talk		<-70dB
Channel impedance		4~16?
Net weight (Kg)		18.5
Produce dimension (LxWxH)mm		430x430x188
Color		Black

## Product Gallery

