

L-412T/L-512T/L-612T/L-812T 4"/5"/6"/8" In Wall/Ceiling Mount Speaker with 1" Mylar Tweeter

Product ID: L-412T/L-512T/L-612T/L-812T



Short Description

Rated power: 10W/20W/30W/40W

Line input: 100V

Speaker driver size: 4" or 5" or 6" or 8" PP + 1" Mylar

Description

ABS in ceiling/wall mount speaker built-in PP cone speaker driver and 1" Mylar tweeter, 100V transformer.

Speaker driver size:

L-412T: 4" PP woofer + 1" Mylar tweeter, Power taps: 5/10W

L-512T: 5" PP woofer + 1" Mylar tweeter, Power taps: 10/20W

L-612T: 6" PP woofer + 1" Mylar tweeter, Power taps: 15/30W

L-812T: 8" PP woofer + 1" Mylar tweeter, Power taps: 20/40W

Specification

Model	L-412T	L-512T	L-612T	L-812T
Rated power	10W	20W	30W	40W
Power taps	5/10W	10/20W	15/30W	20/40W

Line input voltage	100V			
Sensitivity (1m,1W)	87±3dB	88±3dB		
S.P.L.	97dB at 100V 10W		98dB at 100V 10W	
Frequency response	100-20KHz	90-20KHz	80-20KHz	40-20KHz
Woofer speaker driver	4" PP	5" PP	6" PP	8" PP
Tweeter driver	1" Mylar			
Product dimension (mm)	220x146x70	280x192x75	310x223x85	360x256x100
Hole for mounting (mm)	195x120	250x160	275x190	325x220
Frame material	ABS			
Grille material	Powder coated Iron mesh			
Color	White (RAL9016)			
Product net weight (Kg)	1.3	1.6	2.1	2.7
Gross weight	19Kg/12pcs	23Kg/12pcs	20Kg/8pcs	14Kg/4pcs
Packing dimension (cm)	46x33x27	55x43x33	66x41x26	45x39x29

Product Gallery

