

M-170E IP Network POE Active Outdoor Horn Speaker

Product ID: M-170E



Short Description

Rated power: 15W/8?

LAN or WAN connection

POE / DC24V 2A (Standby)

Description

The is an IP network active horn speaker supporting network broadcast intercom system.

It support international standard SIP protocol and can accept broadcasts and calls from LAN and WAN.


It can be quickly deployed to the anyplaces where there is a network cable. With wide sound diffusion angle, it can realize super reproduction of voice and music.

? 10/100M self-adaptive, support DHCP/static IP, support LAN and WAN;

? Support SIP2.0 (RFC3261) and related RFC;

- ? Support narrowband encoding: G.711a/u; broadband encoding: G.722;
- ? Supported audio format: MP3, WAV, FLAC and etc.;
- ? Can play the background music, emergency paging and alarm signal from the host system;
- ? Adopt high-quality ABS plastic, high dynamic range speaker unit, more clear and brighter sound;

Connection diagram:



Specification

Item		Specification
Amplifier OUT	Rated power (RMS)	15W 8?
	SNR	?75dB
	Freq. resp.	350Hz-16KHz
Speaker	Unit driver	2.5?

	Sensitivity	102dB±2dB
	Max. SPL.	115dB±2dB
	Freq. resp.	350Hz-6.3KHz
	Distortion	≤1%
Power	Voltage	POE+(IEEE 802.3at) / DC24V 2A (Standby)
Others	Network interface	RJ45 10/100M?
	Support protocols	DHCP, TCP/IP, UDP, ICMP, IGMP (Multicast), 802.1x, HTTP, HTTPS, FTP, DNS, DDNS, RFC3261, RTP, RTSP, RTCP, UPnP.
	Power interface	24V/2A
	Product dimension (mm)	285x205x288 (L×H×D)
	Product weight (Kg)	1.9Kg
	Gross Weight (Kg)	10.8kg (4pcs)

Product Gallery



