

WS-604WF 4*30W WiFi & Bluetooth Wireless Coaxial Ceiling Speaker



Product ID: WS-604WF



Short Description

Rated power: 4*30W

Line input: 8?

Speaker driver: 6" paper + 1.5" tweeter

With WiFi & LAN & Bluetooth input

With AUX & 100V input

Description

This WiFi active coaxial ceiling speaker system consists 1 master active loudspeaker and 1 sub passive loudspeaker.

Support protocols: AIRPLQY/D LAN/Q PLAY.

Build-in WiFi wireless receiver, can connect with your smart device via app.

Support Bluetooth 5.0 input.

The main loudspeaker builds in 4-channel 4*30W digital Class-D amplifier.

1xRJ45 port available for the point where the WiFi signal is weak.

1 line input for local audio source.

1 100V audio signal input.

2-way coaxial system containing 1x6" woofer and 1x1.5" tweeter.

DC12V power supply with AC adapter.

This speaker system is suitable for AV applications such as meeting rooms, classrooms, multi-media rooms, restaurants, coffee bars, etc.

Specification

Model	WS-602WF	WS-604WF
Rated power	30W×2@8 ohm	30W×4@8 ohm
Speaker driver	6" woofer + 1.5" tweeter	
Amplifier	2-channel digital amplifier (Class D)	
Material	ABS enclosure, metal grille	
Frequency response	80Hz-20KHz/1W, ±3dB	
THD	<0.05% at 1KHz, 1/3 rated power	
S/N	>70dB	
Protocol	HFPV1.5, A2DPV1.2, AVRCPV1.4, HSP1.2, GAVDP1.2, IOP	
Power supply	AC110V-240V/50Hz-60Hz / DC12V	
Power consumption	81W	
Product dimension (mm)	?230*155	
Installing dimension (mm)	?200	
Net weight	4.5Kg (1+1)	9.0Kg (1+3)

Product Gallery

