

H-2400C 2.4G Wireless Conference System Chairman Microphone

Product ID: H-2400C



Short Description

LCD display microphone ID, battery level, microphone state

Microphone touch on/off panel

Priority function

Description

? Wireless & portable table moving

? Electric capacity type microphone, equipped with windshield cover

? LCD display microphone ID, battery level, microphone status, control channel, etc.

? Microphone will shut off the power or in standby if receiver powered off.

? Chairman microphone can be turned on at any time.

? Priority function: chairman can turn off delegate microphones by clear key any time

? Chairman only mode: Delegate microphone can not be turned on again after chairman microphone press priority button. The chairman need quit this mode first, and then delegate microphone can be turned on again

Specification

Items		Parameters
Audio channel	Transmission method	2.4G (one way)
	Audio channel	4 (1 chairman, 3 delegate)
	Carrier frequency band	2400MHz~2483MHz
	Modulation method	FM
	Maximum modulation	60KHz
	Radiant power	?+9dBm
	Frequency deviation	<0.002
	Frequency response	50Hz-15KHz
	S/N Ratio	>95dB
	T.H.D.	<0.8%
Data control channel	Transmission method	2.4g (one-way)
	Data channel	16
	Frequency Range	2400MHz ~ 2483MHz
	Modulation method	FM
	Receiving sensitivity	-100dBm
	Transmission consumption	?6dBm
	Communication rate	100KBPS
	Frequency deviation	<0.002
System	Power supply	DC 3.7V
	Signal covering range	Radius 60 meters
	Consumption Rating	Standby: ?360mW Speaking: ?630mW
	Operating temperature range	-10-40 degree
	Dimensions	170×58×120mm
	N.W	0.7kg