

WS-525WF 5¼" 2*25W Wifi Wireless Wall Mount Speaker



Product ID: WS-525WF



Short Description

Rated power: 2*25W

Line input: 8?

Speaker driver: 5¼" paper + 1½" tweeter

With RJ45, RCA, 6.3mm Mic input

Built-in Wifi wireless receiver

Individual volume control

Description

This 2.0 powered wall mount WiFi speaker is compatible for Android, iOS with APP control. Featured with RJ45 network port for wired connectivity.

This WiFi active wall mount speaker consists of one main active and one sub passive loudspeaker. The main active loudspeaker "L" with built-in 2-channel Class-D stereo amplifier, and built-in WiFi receiver, with Phoenix connector ready to be connected to the sub passive loudspeaker "R".

Suitable for AV applications such as meeting rooms, classrooms, multi-media rooms, restaurants, coffee bars, etc.

Main active loudspeaker "L"

- (1) Built-in 2-channel digital stereo amplifier (Class D) 2*25W.
- (2) Built-in WiFi wireless music streaming receiver.
- (3) Connect with your smart device via the free app.
- (4) One RJ45 port available for the point where the WiFi signal is weaker.
- (5) 2-way speaker drivers woofer 5" + tweeter 1".
- (6) With one 6.35mm MIC jack input.
- (7) "L&R" of unbalanced inputs via RCA connectors.
- (8) 100V signal input via RCA connector available.
- (9) BASS and TREBLE tone controllers.
- (10) Individual volume controls for audio input,WiFi,microphone input,and 100V signal input.

Sub passive loudspeaker "R"

- (1) Rated power 30W.
- (2) 2-way speaker drivers woofer 5" + tweeter 1".
- (3) Phoenix connector ready to be connected to the main loudspeaker "L"

Specification

Model	WS-525WF
Rated power	25W×2@8 ohm
Speaker units	5.25" woofer + 1" tweeter
Build-in amplifier	2-channel digital stereo amplifier (Class D)
Audio inputs	"L&R" of balance inputs via Phoenix connectors
"L&R" of imbalance inputs via RCA connectors	
Material	ABS enclosure, metal bracket & grille
Finished	White & Black available
Frequency response	60Hz-18KHz/1W, ±3dB

T.H.D.	<0.05% at 1kHz, 1/3 rated power
S/N	>95dB
Protection	Over-temperature, overload
Power supply	AC110V-240V/50Hz-60Hz
Dimensions (mm)	170x185x250
Mounting method	"U" shaped bracket adjustable
Net weight	4.8Kg (1+1)

Product Gallery

