

X-NPMK Honeywell Network Paging Console

Product ID: X-NPMK



Short Description

Fulfill zone paging and broadcast control over X-618 broadcast system under the same network

Description

The X-NPMK (Network Paging Console) uses key operation mode to fulfill zone paging and broadcast control over X-618 broadcast system under the same network.

Product Characteristics

- Key operation.
- Removable gooseneck microphone.
- Built-in loudspeaker for zone monitoring and internal communication.
- Audio signal digital processing ensures the audio quality unaffected by transmission path.
- Key modules(X-K8 or X-K4) can be extended as required.

X-NPMK Functions

- Manual Emergency Broadcast
- One-click Broadcast

- Zone/group Broadcast
- Audio Prerecord & Broadcast
- Play Audio Files from USB Disk
- Internal Communication
- Automatic Record
- Microphone and Network Supervision
- Log Function

Specification

Parameters	Values
Power Supply Voltage	DC 24V
Rated Power	11W
Microphone Frequency Response	50Hz-15KHz
SNR	> 85dB
THD	< 0.05%
Microphone Input	-44dB±2dB
Line Input	0dBV (1V)
Line Output	0dBV(1V)
Monitoring Loudspeaker	2W/8 ?
Sample Rate	44.1 KHz, 16Bit
Microphone Pole Length	385 mm
Operation Temperature	-10°C +55°C
Storage Temperature	-40°C +70°C
Humidity	<95%, Non-condensation
Dimension (W×H×D)	200 × 46.5 × 200 mm
Packing Dimension (W×H×D)	403 × 133 × 268mm
Net weight	1.7Kg
Gross weight	2.6Kg