

FS-3521/FS-3641/FS-3851 Premium 5/6.5/8 Inch Outdoor IP66 Waterproof 2-Way Coaxial Wall Mount Speaker

Product ID: FS-3521/FS-3641/FS-3851



Short Description

Rated power: 30W or 40W or 50W

Line input: 70V/100V/8Ω

Speaker driver: 5", 6.5" or 8" Paper+wool Cone + Aluminum dome tweeter

IP66 Waterproof

With optimal bass enhancement radiator

Description

The FS-3521/FS-3641/FS-3851 series outdoor IP66 waterproof wall mount speakers coming PREMIUM 2-way coaxial speaker drivers and exclusive optimal bass enhancement radiator, is a high-quality audio device designed for outdoor use, providing exceptional sound quality and durability in various weather conditions.

LYINTL

FS-3521/FS-3641/FS-3851

High Quality 2-way Coaxial Speaker

Paper+wool Cone Woofer + Aluminum Dome Tweeter

Premium sound experience

Spiral Knots Sound Waves Enhancement Design

Wide angle audio reach (62° vertical and 78° horizontal)

<http://www.lyintl.com>

This outdoor wall mount speakers are coming with very high quality woofer drivers — paper + wool cone and rubber surround, available in 5 inches, 6.5 inches, and 8 inches.

2-way coaxial design combines a Aluminum dome tweeter into the single unit, providing a well-balanced and full-range sound experience. This design is particularly effective in outdoor settings where audio clarity and coverage are essential.



Sonic Optimization Design Elements for

Clean Looks + Sonic Purity

◀ **Premium COAXIAL Speakers**
High Quality 2 Ways Coaxial Speakers for
Exceptional Audio Clarity




The speakers are engineered to deliver premium audio quality, with clear highs and robust lows. It produces rich, immersive sound, making it suitable for various applications such as outdoor parties, events, or background music for outdoor spaces.

Spiral Knots Sound Waves Enhancement Technology

This unique Spiral Knots Sound Waves Enhancement design not only looks good, when work together with the special wide arc on the front housing, it helps create a super wide angle of 62° vertical and 78° horizontal audio reach (normally 30° to 45°).

Spiral Knots Sound Waves Enhancement



Super wide angle audio reach **62° vertical and 78° horizontal**
(normally 30° to 45°)



IP66 Waterproof

The speaker boasts an impressive IP66 rating, making it completely waterproof and dustproof. It can withstand rain, snow, humidity, and other environmental factors, ensuring it continues to perform reliably in challenging outdoor environments.



IP66 Waterproof

FS-3521 / FS-3641 / FS-3851
Waterproof Wall Mount Speaker

5", 6.5" or 8" Paper+wool cone
Aluminum dome tweeter
70V/100V/8Ω line input
PP housing material
With optimal bass enhancement radiator

<http://www.lyintl.com>

Optimal Bass Enhancement Radiator

This speaker comes equipped with an optimal bass enhancement radiator, enhancing the

low-frequency performance. You can expect deep and punchy bass that adds depth and richness to your music or audio.



Durable Construction

Built to withstand outdoor conditions, the speaker features a rugged and durable construction with weather-resistant PP housing materials. It can endure temperature extremes, UV exposure, and moisture without compromising its performance.

The 5/6.5/8 Inch Outdoor IP66 Waterproof 2-Way Coaxial Premium Wall Mount Speaker with Optimal Bass Enhancement Radiator is an excellent choice for outdoor audio enthusiasts. It offers a combination of durability, premium sound quality, and a stylish design, making it an ideal addition to any outdoor entertainment or relaxation space.

Specification

Model	FS-3521	FS-3641	FS-3851
Woofer driver	5" paper+wool cone, rubber surround	6.5" paper+wool co ne, rubber surround	8" paper+wool cone, rubber surround
Tweeter driver	0.75''(20mm) Aluminum dome	0.75''(20mm) Aluminum dome	1''(25mm) Aluminum dome
Frequency range	95Hz-20KHz	95Hz-20KHz	45Hz-20KHz
Power handing	30W	40W	50W

RMS (IEEE219)			
Power handing RMS (program)	60W	80W	80W
Sensitivity	86dB±3	87dB±3	86dB±3
Power taps	30/15/7.5/3.75W/0/8? ?	40/20/10/5W/0/8?	50/25/12.5/6.25W/0/8?
Line input	70V/100V/8?	70V/100V/8?	70V/100V/8?
Termination	Standard pressed connector	Standard pressed connector	Standard pressed connector
Attachment	Brackets, grille	Brackets, grille	Brackets, grille
Dimensions (HxWxDmm)	275x170x168	285x200x195	380x249x280
Housing material	PP	PP	PP
Certificate	IP66 waterproof	IP66 waterproof	IP66 waterproof
Packing dimension (HxWxDcm)	-	-	-

Video



Product Gallery



