

HS-660TS 6.5 Inch 60W 70V/100V/8Ohms Pendant Speaker



Product ID: HS-660TS

Short Description

Rated power: 60W

Line input: 70V/100V/8?

6½" Paper woofer + 1" Silk tweeter

Description

Introducing our cutting-edge 6.5-inch 60W 70V/100V/8? pendant speaker HS-660TS, where fashion meets functionality in the world of audio excellence.

Designed to elevate both home background music systems and commercial public address systems setups, this speaker boasts superior sound quality and impeccable style.

HS-660TS

Fashion design

High quality speaker driver

Clear sound

Crafted with meticulous attention to detail, our pendant speaker HS-660TS seamlessly blends into any interior decoration, adding a touch of sophistication to your space. Its sleek design not only enhances the aesthetics of your environment but also delivers an immersive audio experience that will captivate listeners.

HS-660TS

CE Compliant

PP+Calcium housing

Aluminum grille

Equipped with advanced technology, this speaker ensures crystal-clear sound reproduction across a wide range of frequencies.

With a high power output of 60W and multi power taps, our pendant speaker delivers robust and dynamic sound that fills the room, creating the perfect ambiance for any occasion. Whether it's a cozy evening at home or a lively gathering in a public space, this speaker is designed to meet your audio needs with finesse.

Aluminum grid
Excellent moisture and rust prevention



High quality woofer and tweeter
Ensures crystal-clear sound

Versatile and adaptable, our pendant speaker is suitable for a variety of applications, from residential living rooms to commercial establishments, including restaurants, cafes, retail stores, and more. Its compact size and easy installation make it a convenient choice for any environment.

Specification

Model	HS-660TS
Rated power	60W
Power taps	3.8/7.5/15/30/60W (70V) 7.5/15/30/60W (100V)
Impedance	1.33K \pm 20%/666 \pm 20%/333 \pm 20%/166 \pm 20% (70V) 1.33K \pm 20%/666 \pm 20%/333 \pm 20%/166 \pm 20% (100V)
Line input	70V/100V/8 Ω
SPL	90 \pm 3dB
Frequency response	87-17KHz

Angle of coverage 1KHz (6dB)	167°
Woofer speaker driver	6.5" paper cone
Tweeter speaker driver	1" silk dome
Body material	PP+Calcium
Grille material	Aluminum
Connector type	4 Pin terminal
Speaker mounting method	Hoisting
Speaker mounting hole size	M6 expansion hook
Working temperature	-25°C to +55°C
Storage temperature	-40°C to +70°C
Relative humidity	≤95%
Product size	234*314mm
Net weight	3.95Kg

Product Gallery



