### Phone: +86-20-39390663 - Email: sales@lyintl.com

# H-R1015T 10 Inch 150W Outdoor Weatherproof 2-Way Coaxial PA Stadium Remote Horn Speaker

**Product ID:** H-R1015T



#### **Short Description**

Rated power: 150W

10" LF driver, 1.5" HF driver 8? and 70V/100V for option Ultra-long projection distance

#### **Description**

The H-R1015 series full frequency remote horn professional speaker is designed for strong directivity, impressive SPL, and ultra-long projection distance, ensuring sound reaches farther afield.

Featuring a super-sensitive 1.5" high-frequency unit and impactful 10" low-frequency performance, it delivers precise directivity to control the entire listening area. The sound field is uniform, effectively avoiding destructive sound interference.

8? input and 70V/100V input version for option.

# **Key Features**

• Strong Directivity and Long Projection

Capable of spreading sound over long distances with impressive SPL.

#### • High-Frequency Sensitivity

Equipped with a super-sensitive 1.5" high-frequency unit for clear sound.

#### • Impactful Low-Frequency

Delivers low-frequency sound with significant impact force.

#### • Precise Directivity

Ensures uniform sound distribution, avoiding interference.

#### • Easy Installation

Comes with a simple installation structure and original hoisting parts for easy array formation.

#### • Durable Construction

Made with a high-density fiberglass box to minimize resonance during high-power operation.

## • Versatile Applications

Suitable for both fixed installations and mobile performances.

# **Applications**

The H-R series full frequency remote professional horn loudspeakers are specifically designed for commercial public address occasions requiring long projection distances, ideal for large-scale outdoor sound reinforcement systems. Perfect for stadiums, large theaters, and other vast outdoor environments, its waterproof treatment allows for long-term use in harsh outdoor conditions.

#### **Specification**

Model	H-R1015	H-R1015T

Rated power	150W	150W
Max power	300W	300W
Line input	8?	100V
Sensitivity (1m,1W)	100dB	
Max SPL	120dB	
Frequency response	70Hz-20KHz	
LF driver	10", 51mm voice coil, 140mm magnetic	
HF driver	1.5", 44mm voice coil, 120mm magnetic	
Directivity (HxV)	40°x60°	
Frame material	Glass fiber reinforced plastics	
Grille material	Iron	
Bracket material	Iron	
Input connectors	2 x Neutrik speakon NL4	
Waterproof	IP56	
Color	Black	
Dimension	450 x 450 x 630 mm	
Net weight (Kg)	18	18.2
Gross weight (Kg)	-	-
Packing dimension	-	

# **Product Gallery**

