Phone: +86-20-39390663 - Email: sales@lyintl.com

DA-1060/DA-1120/DA-1240/DA-1360/DA-1480/ DA-1660 1U Single Channel Class D Digital Amplifier Combined with MP3/Bluetooth Player

Product ID:

DA-1060/DA-1120/DA-1240/DA-1480



Short Description

Rated output power: 60W / 120W / 240W / 360W / 480W / 660W Combined with MP3/Bluetooth player Single channel Class-D digital amplifier 1 U slim design

Description

Elevate Your Audio Experience with our Cutting-Edge Amplification Technology

Introducing the DA-1060/DA-1120/DA-1240/DA-1360/DA-1480/DA-1660 series, the ultimate 1U single channel Class D digital amplifiers combined with USB MP3/Bluetooth player. Available in 60W (DA-1060), 120W (DA-1120), 240W (DA-1240), 480W (DA-1480) and 660W (DA-1660) rated power options, these

amplifiers are designed to meet all your audio amplification needs with superior performance and versatility.

Key Features:

• Premium Build Quality:

Featuring a high-quality black aluminum alloy panel, the DA series amplifiers offer a sleek and durable design that complements any setup.

• Enhanced User Interface:

Equipped with silicone touch buttons that are soft, durable, and comfortable to the touch, these amplifiers ensure a superior user experience.

• Efficient Amplification:

The Class D amplifier circuit is engineered for low heat generation and high efficiency, delivering powerful and reliable audio output.

• **Dual Prompt Sounds:**

Choose between two button prompt sounds—bell and alarm—for customized notifications.

• Versatile Signal Inputs:

With five-way signal input options (2 lines and 3 microphones), the DA series amplifiers provide flexible connectivity for various audio sources.

• Advanced Playback Features:

Enjoy seamless audio playback with Bluetooth, USB, and automatic power-on playback functions.

• Clear Display:

A 1.4-inch dot matrix LCD display provides clear and concise information, enhancing usability.

• Remote Control:

Optional infrared remote control functionality allows for convenient operation from a distance.

• Independent Controls:

Adjust the volume, treble, and bass independently for each channel to achieve the perfect audio balance.

• Reliable Power Supply:

The high-performance switching power supply circuit ensures low heat generation and high efficiency, compatible with AC100V-AC240V power supply modes, making it suitable for use worldwide.

• Comprehensive Protection:

Built-in protections include output short circuit protection, DC protection, and high-temperature protection, ensuring the longevity and safety of the amplifier.

Upgrade your audio system with the

DA-1060/DA-1120/DA-1240/DA-1360/DA-1480/DA-1660 series amplifiers, where superior design meets unparalleled functionality. Perfect for professional audio setups, these amplifiers deliver exceptional sound quality and reliability. Experience the difference today!

Specification

| Model | DA-1060 | DA-1120 | DA-1240 | DA-1360 | DA-1480 | DA-1660 | | |
|-------------|---|---------|---------|---------|---------|---------|--|--|
| Rated | 60W | 120W | 240W | 360W | 480W | 660W | | |
| power | | | | | | | | |
| Channel | 1 Channel | | | | | | | |
| Line | 70V/100V/4-16? | | | | | | | |
| output | | | | | | | | |
| Input | MIC1/MIC2/MIC3: 600 Ohms(?) 10mv, balanced/unbalanced | | | | | | | |
| sensitivity | LINE: 10k Ohms(?) 300mv, unbalanced | | | | | | | |
| Output | 0.775V (0 dB) | | | | | | | |
| sensitivity | | | | | | | | |
| Frequency | 60Hz~15kHz (±3dB) | | | | | | | |

| response | | | | | | | | | |
|------------|-------------------------------|-------|-------------------|-------|-------|-------|--|--|--|
| T.H.D. | <0.5% at 1kHz,1/3 rated power | | | | | | | | |
| S/N | MIC: >65dB | | | | | | | | |
| | Line: >80dB | | | | | | | | |
| Tone | BASS: 100Hz (±10dB) | | | | | | | | |
| adjustment | TREBLE: 10kHz (±10dB) | | | | | | | | |
| Power con | 90W | 180W | 360W | 540W | 720W | 990W | | | |
| sumption | | | | | | | | | |
| Power | AC100V~AC240V±10% 50-60Hz | | | | | | | | |
| supply | | | | | | | | | |
| Net weight | 2.4kg | 2.6kg | 3.5kg | 3.7kg | 3.9kg | 4.3kg | | | |
| Gross | 3.0kg | 3.2kg | 4.1kg | 4.3kg | 4.5kg | 4.9kg | | | |
| weight | | | | | | | | | |
| Product | 480 x 200 x 45mm | | 480 x 280 x 45mm | | | | | | |
| dimension | | | | | | | | | |
| Packing | 522 x 284 x 72mm | | 515 x 380 x 100mm | | | | | | |
| dimension | | | | | | | | | |

Product Gallery

