# SUB-808 8 Inch 80W In Celing Mount Subwoofer Speaker with Iron Rear Cover and Power Taps





## **Short Description**

Rated power: 80W

Power taps: 5/10/20/40/80W/0/8?

Line input: 70V/100V/8?

8" paper cone, subber surround

## **Description**

Introducing our **SUB-808 8 Inch 80W In-Ceiling Mount Subwoofer Speaker**, designed to deliver exceptional sound quality and powerful bass. Perfect for high-end background sound systems and home entertainment music systems, this subwoofer combines performance and elegance in a compact form, especially for built-in audio applications in stores, department storesschools, offices, hotels and restaurants.

Simple structure, multiple power options, beautiful black coating and whitemesh surface, stylish and compact appearance can be perfectly integrated with the modern interior decoration.



The panel is made of high-strength ABS material, and therear shell is made of metal technology.

The internal design of the robust and reliable system reflects the extraordinary bass effect, simple and convenient power settings, and easyoperation is suitable for a variety of occasions.

# **Key features:**

#### • Powerful Audio Performance

Equipped with an 8" woofer speaker driver unit and rubber surround for deep, rich bass and low-frequency response from 50Hz to 160Hz (-6dB).

## • Versatile Power Taps

Features 10/20/40/80W power taps at 100V input and 5/10/20/40/80W power taps at 70V input, also support 8 Ohms input, allowing for flexible installation and optimal sound distribution.



#### • Durable Construction

Comes with a magnetic iron grille and slim edge design, along with an iron fireproof rear cover for added safety and durability.

# • Seamless Integration

Designed for in-ceiling mounting, ensuring a sleek and unobtrusive installation that complements any décor.

Enhance your audio experience with the SUB-808, the ideal subwoofer for delivering high-quality sound in both residential and commercial settings.

**Specification** 

Model	SUB-808
Woofer driver	8" paper cone woofer, rubber surround
Frequency range (-6dB)	50Hz-160Hz
(At sensitivity of 90dB)	
Frequency range (-10dB)	50Hz-250Hz
Rated power	80W
Max power	120W
Sensitivity	85dB (1M/1W)
Power taps (100V)	10/20/40/80W
Power taps (70V)	5/10/20/40/80W
Line input	70V/100V/8?
Impedance	8?
Coverage angel	170°
Connector	4-PIN Pluggable terminal
Dimensions (D*H)	?320x245mm
Cut off diameter	?292mm
Material	Iron
Net weight	5.45KG
Gross weight	-
Product dimension (LxWxD)	-
Packing dimension (LxWxD)	-

# **Product Gallery**







