

# RM-20A 6 Zone Remote Paging Microphone for PM-3250Z/PM-3350Z/PM-3500Z/PM-3650Z

**Product ID:** RM-20A



## Short Description

6 Zones independent control  
Paing signal level indication  
Built-in 2 chime tones, chime up and down  
One key for all zones call  
Dual RJ45 connector

## Description

### Professional Paging Microphone for Clear and Reliable Communication

Ensure your messages are heard loud and clear with the [LYINTL](https://www.lyintl.com) RM-20A Remote Paging Microphone. Designed for use in various public address systems, this high-quality paging microphone offers excellent sound clarity and durability, making it ideal for airports, train stations, schools, and commercial buildings.

## Key Features

- **Superior Audio Quality**  
Equipped with a high-sensitivity microphone, the RM-20A captures and transmits voice clearly, ensuring effective communication.

- **Durable Design**  
Built with robust materials to withstand daily use in busy environments.
- **User-Friendly Operation**  
Features a simple push-to-talk button for easy and intuitive use.
- **Long-Range Coverage**  
Provides reliable performance over long distances, making it suitable for large spaces.
- **Flexible Connectivity**  
Compatible with various public address systems and amplifiers, ensuring seamless integration.

## Applications

- **Transportation Hubs**  
Ideal for use in airports, train stations, and bus terminals for clear announcements and communication.
- **Educational Institutions**  
Perfect for schools and universities to facilitate communication during events and emergencies.
- **Commercial Spaces**  
Suitable for shopping malls, office buildings, and retail stores for announcements and paging.
- **Industrial Settings**  
Excellent for factories and warehouses, enabling effective communication in noisy environments.

Enhance your public address system with [LYINTL RM-20A Remote Paging Microphone](#). Its superior audio quality, durable construction, and user-friendly operation make it the perfect choice for any professional communication setup.

## Specification

Model	RM-20A
Sensitivity	30±3mV
Frequency response	200Hz-15KHz
SNR	≥70db
Communication	RS485, RJ45 connector
Net weight	0.9kg
Gross weight	1.6kg
Product dimension (HxWxD)	172x160x53mm
Packing dimension (HxWxD)	425x285x115mm

**Product Gallery**

