
























Honeywell PA/AV System

No.	Model	Product	Image	Short Description	MOQ (pcs)	Total Price (USD)
1	X-DCS2000	Honeywell Digital Integrated System Manager		Supports manual selection source Supports emergency mic input 4 AUX input, 8 zone output	1	
2	X-DCS3000				1	
3	HN-PTT	Honeywell Push-to-talk Microphone		Superior voice reproduction Dynamic transduce Remote switching contact	1	
4	X-DA1500EN	Honeywell High Efficiency Class D Digital Power Amplifier (1*500W)		X-DA1500/X-DA1500EN (1x500W)	1	
5	X-DA2250EN	Honeywell High Efficiency Class D Digital Power Amplifier (2*250W)		X-DA2250/X-DA2250EN (2x250W)	1	
6	X-DA4125EN	Honeywell High Efficiency Class D Digital Power Amplifier (4*125W)		X-DA4125/X-DA4125EN (4x125W)	1	
7	X-DA1500	Honeywell High Efficiency Class D Digital Power Amplifier (1*500W)		X-DA1500/X-DA1500EN (1x500W)	1	
8	X-DA2250	Honeywell High Efficiency Class D Digital Power Amplifier (2*250W)		X-DA2250/X-DA2250EN (2x250W)	1	
9	X-DA4125	Honeywell High Efficiency Class D Digital Power Amplifier (4*125W)		X-DA4125/X-DA4125EN (4x125W)	1	
10	X-DA4060	Honeywell High Efficiency Class D Digital Power Amplifier (4*60W)		X-DA4060/X-DA4060EN (4x125W)	1	
11	X-NPMI	Honeywell Configurable Network Paging Console		Provide paging, monitoring Built-in monitor loudspeaker Touch screen operation	1	Phase out
	X-NPMK	Honeywell Network paging console		Network paging console (not configurable)	1	
12	X-NPMS	Honeywell Configurable Network Paging Console		Configurable Network Paging Console 7" TFT Touch Screen Suitable for Desktop Flush Mount	1	
13	X-MAP4P	Honeywell Digital Multi-audio Player		Integrated with DVD/USB/SD Support Mp3/FM/AM tuner 2 DVD/USB/SD/FM lines output	1	
14	X-NRI/EN	Honeywell Network Resource Interface		4 AUX input 512MB Flash memory 4G SD card internal audio source	1	
1	X-SPT900	X-SMART Med to Small Project System Management Software Package (Include 1 server and 1 client interface)		X-SMART Med to Small Project System Management Software Package (Include 1 server and 1 client interface)	1	

Howneywell EN54-24 Loudspeaker

No.	Model	Product	Image	Short Description	MOQ (pcs)	Total Price (USD)
	L-PCM06A	5" ceiling loudspeaker, 6/3/1.5W, white, metal		Rated power: 6W Power taps: 1.5/3/6W @ 100V 0.75/1.5/3W @ 70V Speaker driver: 5" dual-cone	200	
	L-PCM06B	6.5" Ceiling loudspeaker, 6/3W, white, Metal, Metal dome		Rated power: 6W Power taps: 1.5/3/6W @ 100V 0.75/1.5/3W @ 70V Speaker driver: 6.5"	200	
2	L-VCM24A/EN	Honeywell 24W 6.5" 2-Way Fireproof Metal Ceiling Speaker EN54-24		Rated power: 24W Speaker unit: 2-way 6.5" Comply with EN54-24 standard	200	
3	L-VCM6A/EN	Honeywell 6W 6.5" Fireproof Metal Ceiling Speaker EN54-24		Rated power: 6W Speaker unit: 6.5" Comply with EN54-24 standard	200	
4	L-VCM6B/EN	Honeywell 6W 5" Fireproof Metal Ceiling Speaker EN54-24		Rated power: 6W Speaker unit: 5" Comply with EN54-24 standard	200	
NEW!	L-VCP06A/EN	Honeywell 6W 5" Ceiling Loudspeaker with Fire Dome EN54-24		Rated power: 6W Speaker unit: 5" Comply with EN54-24 standard	200	
9	L-VWM06A/EN	Honeywell 4" Fireproof Metal Cabinet Speaker EN54-24		Rated power: 6W Speaker unit: 4" Comply with EN54-24 standard	200	
	L-PWP60A	Wall mount cabinet loudspeaker, 60/30/15W, white, ABS		Rated power: 60W Power taps: 15/30/60W @ 100V 7.5/15/30W @ 70V Speaker driver: 6.5" + 1"	200	
6	L-VJM10A/EN	Honeywell 10W Aluminum Unidirectional Projection Loudspeaker		Rated power: 10W Meets outdoor requirements EN54-24 certified, IP65 standard	200	
1	L-VBM20A/EN	Honeywell 20W Aluminum Bidirectional Projection Loudspeaker		Rated power: 20W (10Wx2) Meets outdoor requirements EN54-24 certified, IP65 standard	200	
5	L-VHP15A/EN	Honeywell 15W Horn Loudspeaker		Rated power: 15W Meets outdoor requirements EN54-24 certified, IP66 standard	200	
7	L-VOM20A/EN	Honeywell 20W Aluminum Outdoor Column Loudspeaker		Rated power: 20W Robust Aluminum material EN54-24 certified, IP66 standard	200	
8	L-VOM40A/EN	Honeywell 40W Aluminum Outdoor Column Loudspeaker		Rated power: 40W Robust Aluminum material EN54-24 certified, IP66 standard	200	