



























Ceiling Speaker

No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	L-213	2.5" 6W ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 2½" paper cone	300	
2	L-223	2.5" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 2½" paper cone	300	
3	L-243	4" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 4" paper	300	
4	L-243H	4" 6W Iron Ceiling Speaker with Iron Back Cover		Rated power: 6W Line input: 100V Speaker driver: 4" paper	300	
5	L-3011	3" 6W Mini Frameless Ceiling Speaker		Rated power: 6W Line input: 70V/100V 3" full range paper cone driver Mini frameless design	300	
6	L-3503	4.5" 10W Steel Ceiling Speaker		Rated power: 10W Line input: 70V/100V 4½" paper cone	300	
7	L-3803	6.5" 10W Steel Ceiling Speaker		Rated power: 10W Line input: 70V/100V 6½" paper cone	300	
8	L-3801	8" 30W 2-Way ABS Coaxial Ceiling Speaker		Rated power: 30W Line input: 70V/100V 8" paper cone woofer + 1" tweeter	300	
10	L-431	4" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 4"	200	
11	L-531	5" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 5"	200	
12	L-631	6" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 6"	200	
13	L-5011	6½" 10W ABS Slim Edge Ceiling Speaker (100V)		Rated power: 10W Line input: 70V/100V Speaker driver: 6½" paper cone	300	
14	L-6011	6W 6.5" Frameless Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 6½" paper cone	300	
15	L-5012	8" 35W ABS Slim Edge Coaxial Ceiling Speaker		Rated power: 35W Line input: 70V/100V Speaker driver: 8" woofer + ¾" tweeter	300	
16	L-5211	6½" 10W ABS Slim Edge Coaxial Ceiling Speaker		Rated power: 10W Line input: 70V/100V Speaker driver: 6" woofer + ¾" tweeter	300	
17	L-505T	5" 6W ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 5"	300	
18	L-605T	6" 6W ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 6"	300	
19	L-805T	8" 6W ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 8"	300	











20	L-507T	5" Ceiling Speaker with 1/2" Mylar Rotatable Tweeter		Rated power: 20W Line input: 100V 5" PP woofer + 1/2" Mylar rotatable tweeter	300	
21	L-607T	6" Ceiling Speaker with 1/2" Mylar Rotatable Tweeter		Rated power: 30W Line input: 100V 6" PP woofer + 1/2" Mylar rotatable tweeter	300	
22	L-807T	8" Ceiling Speaker with 1/2" Mylar Rotatable Tweeter		Rated power: 40W Line input: 100V 8" PP woofer + 1/2" Mylar rotatable tweeter	300	
23	L-511T	5" Ceiling Speaker with 1/2" Mylar Tweeter		Rated power: 20W Line input: 100V 5" PP woofer + 1/2" Mylar tweeter	300	
24	L-611T	6" Ceiling Speaker with 1/2" Mylar Tweeter		Rated power: 30W Line input: 100V 6" PP woofer + 1/2" Mylar tweeter	300	
25	L-811T	8" Ceiling Speaker with 1/2" Mylar Tweeter		Rated power: 40W Line input: 100V 8" PP woofer + 1/2" Mylar tweeter	300	
26	L-526T	5" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 5"	300	
27	L-626T	6.5" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 6 1/2"	300	
28	L-826T	8" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver size: 8"	300	
29	L-556T	5" Slim Edge ABS Ceiling Speaker with Silk Tweeter		Rated power: 20W Line input: 100V 5" Paper woofer + 1/4" silk tweeter	300	
30	L-656T	6" Slim Edge ABS Ceiling Speaker with Silk Tweeter		Rated power: 30W Line input: 100V 6" Paper woofer + 1/4" silk tweeter	300	
31	L-856T	8" Slim Edge ABS Ceiling Speaker with Silk Tweeter		Rated power: 40W Line input: 100V 8" Paper woofer + 1" silk tweeter	300	
32	L-608TA	6.5" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 6 1/2" paper cone	300	
33	L-621	6" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 6" paper cone	300	
34	L-623	5" ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 5" paper cone	300	
35	L-603	6" ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 6" paper cone	300	
36	L-613	8" ABS Ceiling Speaker		Rated power: 10W Line input: 100V Speaker driver: 8" paper cone	300	
37	L-650T	6.5" 10W On Ceiling Mount Speaker		Rated power: 10W Line input: 100V Woofer driver: 6 1/2" paper cone	300	
38	L-663T	6" 6W ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 6" paper	300	
39	L-821	8" 6W Iron Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 8" paper cone	300	
40	L-A124	6 1/2" 10W ABS Ceiling Speaker		Rated power: 10W Line input: 70V/100V Speaker driver: 6 1/2" paper cone	300	
41	LS-213	2.5" 6W Slim Edge Ceiling Speaker		Rated power: 6W Line input: 100V 2.5" full range paper cone driver Slim edge design	300	










42	LS-503	5" Slim Edge ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 5" paper cone Slim edge design	300	
43	LS-603	6" Slim Edge ABS Ceiling Speaker		Rated power: 6W Line input: 100V Speaker driver: 6" paper cone Slim edge design	300	
44	LS-803	8" Slim Edge ABS Ceiling Speaker		Rated power: 10W Line input: 100V Speaker driver: 8" paper cone Slim edge design	300	




Remarks:

- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.

Ceiling Speaker with Rear Cover

No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	L-431H	4" 6W Iron Ceiling Speaker with Iron Back Cover		Rated power: 6W Line input: 100V Speaker driver size: 4" paper	300	
2	L-531H	5" 6W Iron Ceiling Speaker with Iron Back Cover		Rated power: 6W Line input: 100V Speaker driver size: 5" paper	300	
3	L-631H	6" 6W Iron Ceiling Speaker with Iron Back Cover		Rated power: 6W Line input: 100V Speaker driver size: 6" paper	300	stopped
4	L-443K	4" 6W Waterproof Ceiling Speaker IP55		Rated power: 6W Line input: 100V Waterproof: IP55	300	
5	L-621H	6" 6W Iron Ceiling Speaker with Iron Back Cover		Rated power: 6W Line input: 100V Speaker driver: 6" paper cone	300	
6	L-821H	8" 6W Iron Ceiling Speaker with Iron Back Cover		Rated power: 6W Line input: 100V Speaker driver: 8" paper cone	300	
7	LS-443K	4" 6W Slim Edge Waterproof Ceiling Speaker IP55		Rated power: 6W Line input: 100V Slim edge design Waterproof: IP55	300	
8						
9	LS-503K	5" 6W Slim Edge Ceiling Speaker with ABS Cover		Rated power: 6W Line input: 100V Speaker driver: 5" paper cone Slim edge design	300	
10	LS-603K	6" 6W Slim Edge Ceiling Speaker with ABS Cover		Rated power: 6W Line input: 100V Speaker driver: 6" paper cone Slim edge design	300	
11	L-406TKS	4" Ceiling Speaker with ABS Cover and Power Taps		Rated power: 20W Line input: 70V/100V/8Ω 4" PP woofer + 1" Mylar tweeter	300	
12	L-506TKS	5" Ceiling Speaker with ABS Cover and Power Taps		Rated power: 30W Line input: 70V/100V/8Ω 5" PP woofer + 1" Mylar tweeter	300	
13	L-606TKS	6" Ceiling Speaker with ABS Cover and Power Taps		Rated power: 40W Line input: 70V/100V/8Ω 6" PP woofer + 1" Mylar tweeter	300	
14	L-429	4" 25W Iron Ceiling Speaker with 1" Tweeter and Iron Back Cover		Rated power: 25W Line input: 70V/100V/8Ω 4" PP woofer + 1" PEN tweeter	300	
15	L-507THS	5" Ceiling Speaker with 1/2" Mylar Rotatable Tweeter, Iron Back Cover and Power Taps		Rated power: 20W Line input: 70V/100V/8Ω 5" PP woofer + 1/2" Mylar rotatable tweeter	320	
16	L-607THS	6" Ceiling Speaker with 1/2" Mylar Rotatable Tweeter, Iron Back Cover and Power Taps		Rated power: 30W Line input: 70V/100V/8Ω 6" PP woofer + 1/2" Mylar rotatable tweeter	320	
17	L-807THS	8" Ceiling Speaker with 1/2" Mylar Rotatable Tweeter, Iron Back Cover and Power Taps		Rated power: 40W Line input: 70V/100V/8Ω 8" PP woofer + 1/2" Mylar rotatable tweeter	320	
18	L-511THS	5" Ceiling Speaker with 1/2" Mylar Tweeter, Iron Back Cover and Power Taps		Rated power: 20W Line input: 70V/100V/8Ω 5" PP woofer + 1/2" Mylar tweeter	300	
19	L-611THS	6" Ceiling Speaker with 1/2" Mylar Tweeter, Iron Back Cover and Power Taps		Rated power: 30W Line input: 70V/100V/8Ω 6" PP woofer + 1/2" Mylar tweeter	300	
20	L-811THS	8" Ceiling Speaker with 1/2" Mylar Tweeter, Iron Back Cover and Power Taps		Rated power: 40W Line input: 70V/100V/8Ω 8" PP woofer + 1/2" Mylar tweeter	300	











21	L-511TKS	5" Ceiling Speaker with 1/2" Mylar Tweeter, ABS Back Cover and Power Taps		Rated power: 20W Line input: 70V/100V/8Ω 5" PP woofer + 1/2" Mylar tweeter	300	
22	L-611TKS	6" Ceiling Speaker with 1/2" Mylar Tweeter, ABS Back Cover and Power Taps		Rated power: 30W Line input: 70V/100V/8Ω 6" PP woofer + 1/2" Mylar tweeter	300	
23	L-811TKS	8" Ceiling Speaker with 1/2" Mylar Tweeter, ABS Back Cover and Power Taps		Rated power: 40W Line input: 70V/100V/8Ω 8" PP woofer + 1/2" Mylar tweeter	300	
24	L-519THS	5" 20W Ceiling Speaker with 1/2" Mylar Tweeter, Iron Back Cover and Power Taps		Rated power: 20W Line input: 70V/100V/8Ω Woofer driver: 5" PP cone, 1/2" Mylar tweeter	300	
25	L-526TH	5" 6W Iron Ceiling Speaker with Iron Cover		Rated power: 6W Line input: 100V Speaker driver size: 5"	300	
26	L-626TH	6.5" 6W Iron Ceiling Speaker with Iron Cover		Rated power: 6W Line input: 100V Speaker driver size: 6 1/2"	300	
27	L-826TH	8" 6W Iron Ceiling Speaker with Iron Cover		Rated power: 6W Line input: 100V Speaker driver size: 8"	300	
28	L-531I	Surface Mount Ceiling Speaker		Rated power: 10W Line input: 70V/100V Woofer driver: 6 1/2" paper cone	300	
29	L-3409	4.5" 15W Steel Fireproof Ceiling Speaker		Rated power: 15W Line input: 70V/100V Speaker driver: 4 1/2" paper cone	300	
30	L-3410	4 1/2" 6W Steel Fireproof Ceiling Speaker		Rated power: 6W Line input: 70V/100V Speaker driver: 4 1/2" paper cone	300	
31	L-341I	4.5" 6W Steel Fireproof Ceiling Speaker		Rated power: 6W Line input: 70V/100V Speaker driver: 4 1/2"	300	
32	L-361I	6.5" 10W Steel Fireproof Ceiling Speaker		Rated power: 10W Line input: 70V/100V Speaker driver: 6 1/2" paper	300	
33	L-457THS	4" Ceiling Speaker with Silk Tweeter, Iron Back Cover and Power Taps		Rated power: 20W Line input: 70V/100V/8Ω 4" woofer + 3/4" silk tweeter	300	
34	L-657THS	6.5" Ceiling Speaker with Silk Tweeter, Iron Back Cover and Power Taps		Rated power: 30W Line input: 70V/100V/8Ω 6 1/2" woofer + 1" silk tweeter	300	
35	L-857THS	8" Ceiling Speaker with Silk Tweeter, Iron Back Cover and Power Taps		Rated power: 60W Line input: 70V/100V/8Ω 8" woofer + 1" silk tweeter	300	
36	L-401THS	4" 20W Fireproof In-ceiling Speaker with Iron Rear Cover		Rated power: 20W Line input: 70V/100V/8Ω Speaker driver: 4" Graphite + 0.75" Silk Power taps: 2.5/5/10/20W	200	
37	L-501THS	5" 30W Fireproof In-ceiling Speaker with Iron Rear Cover		Rated power: 30W Line input: 70V/100V/8Ω Speaker driver: 5" Graphite + 0.75" Titanium Power taps: 7.5W-3.75/7.5/15/30W (Tweeter is rotatable)	200	
38	L-601THS	6.5" 40W Fireproof In-ceiling Speaker with Iron Rear Cover		Rated power: 40W Line input: 70V/100V/8Ω Speaker driver: 6.5" Graphite + 1" Titanium Power taps: 5/10/20/40W (Tweeter is rotatable)	200	









39	L-408THS	4" 20W In-ceiling Speaker with ABS Rear Cover		Rated power: 20W Line input: 70V/100V/8Ω Speaker driver: 4" Graphite + 0.75" PEI Power taps: 2.5/5/10/20W	200	
40	L-508THS	5" 30W In-ceiling Speaker with ABS Rear Cover		Rated power: 30W Line input: 70V/100V/8Ω Speaker driver: 5" Graphite + 0.75" PEI Power taps: 3.75/7.5/15/30W	200	
41	L-608THS	6.5" 40W In-ceiling Speaker with ABS Rear Cover		Rated power: 40W Line input: 70V/100V/8Ω Speaker driver: 6.5" Graphite + 1" PEI Power taps: 5/10/20/40W	200	
42	L-402H	4" 20W In-ceiling Speaker with Iron Rear Cover (8Ω)		Rated power: 20W Impedance: 8Ω Speaker driver: 4" Graphite + 0.5" PEI Taps: 8ohm-NC-20W-10W-5W-2.5W	200	
43	L-602THS	6.5" 40W In-ceiling Speaker with Iron Rear Cover (70V/100V/8Ω)		Rated power: 40W Line input: 70V/100V/8Ω Speaker driver: 6.5" Graphite + 1" Titanium Taps: 8ohm-NC-40W-20W-10W-5W	200	
44	L-802THS	8" 50W In-ceiling Speaker with Iron Rear Cover (70V/100V/8Ω)		Rated power: 50W Line input: 70V/100V/8Ω Speaker driver: 8" Graphite + 1" Titanium Taps: 8ohm-NC-50W-25W-12.5W-6.25W	200	
45	LS-532	5" 30W In-ceiling Speaker with ABS Rear Cover and Power Taps		Rated power: 30W Line input: 70V/100V/8Ω Speaker driver: 5" Graphite woofer + 1" Silk tweeter Power taps: 3.75/7.5/15/30W	200	
46	LS-642	6" 40W In-ceiling Speaker with ABS Rear Cover and Power Taps		Rated power: 40W Line input: 70V/100V/8Ω Speaker driver: 6" Graphite woofer + 1" silk tweeter Power taps: 5/10/20/40W	200	
47	LS-852	8" 50W In-ceiling Speaker with ABS Rear Cover and Power Taps		Rated power: 50W Line input: 70V/100V/8Ω Speaker driver: 8" Graphite woofer + 1" silk tweeter Power taps: 6.25/12.5/25/50W	200	




Remarks:

- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.

Wall Mount Speaker

No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	FS-3118	Home Theater Mini Wall Mount Satellite Speaker		Rated power: 10W/8Ω 2.75" woofer speaker driver With quick installation bracket	500	
2	FS-3119	Fashion Mini Wall Mount PA Speaker		Rated power: 10W/100V 2.75" woofer speaker driver With quick installation bracket	500	
3	FS-31S	3" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 15W Line input: 70V/100V/4Ω Woofer speaker driver: 3"	300	
4	FS-51S	5" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 30W Line input: 70V/100V/4Ω Woofer speaker driver: 5"	300	
5	FS-3520	30W Outdoor Waterproof Wall Mount Speaker		Rated power: 30W Line input: 70V/100V/8Ω Speaker driver: 5"+1" Waterproof IP65	300	
6	FS-3640	40W Outdoor Waterproof Wall Mount Speaker		Rated power: 40W Line input: 70V/100V/8Ω Speaker driver: 6.5"+1" Waterproof IP65	300	
7	FS-3850	50W Outdoor Waterproof Wall Mount Speaker		Rated power: 50W Line input: 70V/100V/8Ω Speaker driver: 8"+1" Waterproof IP65	300	
8	FS-6430	4.5" 30W Outdoor All Weather Waterproof Wall Mount Speaker		Rated power: 30W Line input: 70V/100V/8Ω 4½" woofer + 1" silk soft dome IP66 All weatherproof	200	
9	FS-6640	6.5" 40W Outdoor All Weather Waterproof Wall Mount Speaker		Rated power: 40W Line input: 70V/100V/8Ω 6½" woofer + 1" silk soft dome IP66 All weatherproof	200	
10	F-6850	8" 40W Outdoor All Weather Waterproof Wall Mount Speaker		Rated power: 50W Line input: 70V/100V/8Ω 8" woofer + 1" silk soft dome IP66 All weatherproof	200	
11	F-23S	3" 6W On Wall Mount Cabinet Speaker with Power Taps		Rated power: 6W Line input: 70V/100V/8Ω Speaker driver: 3" PP + 1" Mylar	300	
12	F-31	3" On Wall Mount Cabinet Speaker		Rated power: 15W Line input: 100V Speaker driver: 3½" PP + 1" tweeter	300	
13	F-41	4" On Wall Mount Cabinet Speaker		Rated power: 20W Line input: 100V Speaker driver: 4" PP + 1" tweeter	300	
14	F-51	5" On Wall Mount Cabinet Speaker		Rated power: 30W Line input: 100V Speaker driver: 5" PP + 1" tweeter	300	
15	F-61	6" On Wall Mount Cabinet Speaker		Rated power: 40W Line input: 100V Speaker driver: 6" PP + 1" tweeter	300	
16	F-31S	3" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 15W Power taps: 2.5/5/10/15W/0/8Ω Line input: 70V/100V/8Ω Speaker driver: 3½" PP + 1" tweeter	300	
17	F-41S	4" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 20W Power taps: 2.5/5/10/20W/0/8Ω Line input: 70V/100V/8Ω Speaker driver: 4" PP + 1" tweeter	300	
18	F-51S	5" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 30W Power taps: 3.75/7.5/15/30W/0/8Ω Line input: 70V/100V/8Ω Speaker driver: 5" PP + 1" tweeter	300	
19	F-61S	6" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 40W Power taps: 5/10/20/40W/0/8Ω Line input: 70V/100V/8Ω Speaker driver: 6" PP + 1" tweeter	300	













20	F-45	4" On Wall Mount Cabinet Speaker		Rated power: 20W Line input: 100V Speaker driver: 4" PP + 1" tweeter	300	
21	F-55	5" On Wall Mount Cabinet Speaker		Rated power: 30W Line input: 100V Speaker driver: 5" PP + 1" tweeter	300	
22	F-65	6" On Wall Mount Cabinet Speaker		Rated power: 40W Line input: 100V Speaker driver: 6" PP + 1" tweeter	300	
23	F-85	8" On Wall Mount Cabinet Speaker		Rated power: 60W Line input: 100V Speaker driver: 8" PP + 1" tweeter	300	
24	F-45S	4" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 20W Line input: 70V/100V/8Ω Speaker driver: 4" PP + 1" tweeter	300	
25	F-55S	5" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 30W Line input: 70V/100V/8Ω Speaker driver: 5" PP + 1" tweeter	300	
26	F-65S	6" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 40W Line input: 70V/100V/8Ω Speaker driver: 6" PP + 1" tweeter	300	
27	F-85S	8" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 60W Line input: 70V/100V/8Ω Speaker driver: 8" PP + 1" tweeter	300	
28	F-47S	4" 20W On Wall Mount Cabinet Speaker with Power Taps		Rated power: 20W Line input: 70V/100V/8Ω Speaker driver: 4" PP + 1" PEI	300	
29	F-49S	4" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 20W Line input: 70V/100V/8Ω Speaker driver: 4" + 1" tweeter	300	
31	F-69S	6 1/2" On Wall Mount Cabinet Speaker with Power Taps		Rated power: 60W Line input: 70V/100V/8Ω Speaker driver: 6 1/2" + 1" tweeter	300	
32	F-530T	5" 30W Fashion Wall Mount Speaker		Rated power (100V): 3.75W/7.5W/15W/30W Rated power (70V): 1.8W/3.75W/7.5W/15W/30W Max. power: 60W Input: 70V/100V/8Ω Sensitivity (1W/1M): 91dB±3dB Fre. Response: 130Hz-15KHz Speaker unit: LF: 5"x1 TF: 1"x1 Dimension (H*W*D): 295x196x157mm	200	
33	FS-440T	4 1/2" 40W/100V Outdoor Wall Mount Speaker		Rated power (100V): 40W Max. power: 80W Input: 100V Sensitivity (1W/1M): 92dB±3dB Fre. Response: 90KHz -16KHz Speaker unit: LF: 44.5"x1 TF: 0.75"x1 Dimesion (H*W*D): 145x240x190mm Net Weight: 1.8CKG		
34	FS-440TS	4 1/2" 40W Outdoor Wall Mount Speaker with Power Taps		Rated power (100V): 5W/10W/20W/40W Rated power (70V): 2.5W/5W/10W/20W/40W Rated powe (8Ω): 40W Max. power: 80W Input: 70V/100V/8Ω Sensitivity (1W/1M): 92dB±3dB Fre. Response: 90Hz-16KHz Speaker unit: LF: 4.5"x1 TF: 0.75"x1 Dimension (H*W*D): 145x240x190mm Net Weight: 1.82KG		
35	F-904T	4 1/2" 20W Wall Mount PA Speaker with Power Taps		Rated power: 20W Line input: 70V/100V/8Ω Speaker driver: 4.5" + 0.75" tweeter		
36	F-905T	5" 30W Wall Mount PA Speaker with Power Taps		Rated power: 30W Line input: 70V/100V/8Ω Speaker driver: 5.5" + 1" tweeter		




37	FS-640	6.5" 40W Wall Mount Speaker		<p>Rated power (100V): 5W/10W/20W/40W Rated power (70V): 2.5W/5W/10W/20W/40W Rated power (8Ω): 40W Max. power: 80W Input: 70V/100V/8Ω Sensitivity (1W/1M): 94dB±3dB Fre. Response: 100-15KHz Speaker unit: LF: 6.5"x1" TF: 1"x1" Dimension (H*W*D): Net Weight: 3.5KG</p>	200	
38	F-8062	4" On Wall Mount Cabinet Speaker		<p>Rated power: 20W Line input: 70V/100V/8Ω Speaker driver: 4" + 1" tweeter</p>	300	
39	F-8063	5" On Wall Mount Cabinet Speaker		<p>Rated power: 30W Line input: 70V/100V/8Ω Speaker driver: 5" + 1" tweeter</p>	300	
40	F-8064	6.5" On Wall Mount Cabinet Speaker		<p>Rated power: 40W Line input: 70V/100V/8Ω Speaker driver: 6.5" + 1" tweeter</p>	300	
41	FS-4420	4" 20W 2-way Outdoor Waterproof Wall Mount Speaker with Power Taps		<p>Power taps: 20W Power taps: 4/8/15/20W Line input: 70V/100V/8Ω Speaker driver: 4" + 1" IP66 Waterproof</p>	300	

Remarks:

1. Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
2. Price validity period is 30 days.
3. Product quality warranty period is 1 year.
4. OEM is available.




Wall Mount Speaker

No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	W-03	2.5" 3W On Wall Mount Waterproof Speaker		Rated power: 3W Line input: 100V Speaker driver: 2.5" Mylar cone	300	
2	W-102	6.5" 6W On Wall Mount ABS Cabinet Speaker		Rated power: 6W Line input: 100V Speaker driver: 6.5" paper cone	300	
3	W-107	6.5" 10W On Wall Mount ABS Cabinet Speaker		Rated power: 10W Line input: 100V Speaker driver: 6.5" paper cone	300	
4	W-104	5" 6W On Wall Mount ABS Speaker		Rated power: 6W Line input: 100V Speaker driver: 5" paper cone	300	stopped
5	W-105	6.5" 10W On Wall Mount ABS Cabinet Speaker		Rated power: 10W Line input: 100V Speaker driver: 6.5" paper	300	
6	W-106II	6.5" 10W On Wall Mount ABS Cabinet Speaker		Rated power: 10W Line input: 100V Speaker driver: 6.5"	300	
7	W-108	6.5" 10W On Wall Mount ABS Cabinet Speaker		Rated power: 10W Line input: 100V Speaker driver: 6.5" paper	300	
8	W-109	6.5" On Wall Mount ABS Cabinet Speaker		Rated power: 10W Line input: 100V Speaker driver: 6.5" paper cone	300	
9	W-119	5.5" On Wall Mount ABS Cabinet Speaker		Rated power: 6W Line input: 100V Speaker driver: 5.5" paper cone	300	
10	W-115	6.5" 10W On Wall Mount ABS Cabinet Speaker		Rated power: 10W Line input: 100V Speaker driver: 6.5" paper	300	
11	W-116II	4.5" 6W On Wall Mount ABS Speaker		Rated power: 6W Line input: 70V/100V Speaker driver: 4.5" KSV cone	300	
12	W-117	4.5" 10W On Wall Mount ABS Speaker		Rated power: 10W Line input: 70V/100V Speaker driver: 4.5" KSV cone	300	
13	W-3404	4" 40W Flabellate Wall Mount Speaker		Rated power: 40W Line input: 70V/100V/4Ω Speaker driver: 4" PP cone + 1" silk tweeter	300	
14	WS-3404	4" All Weatherproof Landscape Speaker Wall Mount		Rated power: 20W Line input: 70V/100V/8Ω 4" woofer + 0.75" tweeter IP66 All weatherproof	300	
15	WS-3504	5.25" All Weatherproof Landscape Speaker Wall Mount		Rated power: 30W Line input: 70V/100V/8Ω 5.25" woofer + 1" tweeter IP66 All weatherproof	300	
16	WS-3604	6.5" All Weatherproof Landscape Speaker Wall Mount		Rated power: 40W Line input: 70V/100V/8Ω 6.5" woofer + 1" tweeter IP66 All weatherproof	300	
17	W-502T	5.5" 6W On Wall Mount Cabinet Speaker		Rated power: 6W Line input: 100V Speaker driver: 5.5" paper cone	300	

18	W-503T	5" 6W On Wall Mount Metal Cabinet Speaker		Rated power: 6W Line input: 100V/4Ω Speaker driver: 5" paper cone	300	
19	W-505T	5" 10W On Wall Mount Flat Speaker		Rated power: 10W(100V), 20W(4Ω) Line input: 100V/4Ω Speaker driver: 5" ASV cone	200	
20	W-514T	5" 6W On Wall Mount Metal Cabinet Speaker		Rated power: 6W Line input: 100V Speaker driver: 5" paper cone	300	

Remarks:









- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.


In-wall Mount Speaker						
No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	L-412T	4" In Wall/Ceiling Mount Speaker with 1" Mylar Tweeter		Rated power: 10W Line input: 100V Speaker driver size: 4" PP + 1" Mylar	300	
2	L-512T	5" In Wall/Ceiling Mount Speaker with 1" Mylar Tweeter		Rated power: 20W Line input: 100V Speaker driver size: 5" PP + 1" Mylar	300	
3	L-612T	6" In Wall/Ceiling Mount Speaker with 1" Mylar Tweeter		Rated power: 30W Line input: 100V Speaker driver size: 6" PP + 1" Mylar	300	
4	L-812T	8" In Wall/Ceiling Mount Speaker with 1" Mylar Tweeter		Rated power: 40W Line input: 100V Speaker driver size: 8" PP + 1" Mylar	300	
5	L-518T	5" In Wall/Ceiling Mount Speaker with 1/2" Mylar Tweeter		Rated power: 20W Line input: 100V Speaker driver size: 5" PP + 1/2" Mylar	300	
6	L-618T	6" In Wall/Ceiling Mount Speaker with 1/2" Mylar Tweeter		Rated power: 30W Line input: 100V Speaker driver size: 6" PP + 1/2" Mylar	300	
7	L-818T	8" In Wall/Ceiling Mount Speaker with 1/2" Mylar Tweeter		Rated power: 40W Line input: 100V Speaker driver size: 8" PP + 1/2" Mylar	300	
8	L-528T	5" In Wall/Ceiling Mount Speaker		Rated power: 6W Line input: 100V Speaker driver size: 5" paper cone	300	
9	L-628T	6" In Wall/Ceiling Mount Speaker		Rated power: 6W Line input: 100V Speaker driver size: 6" paper cone	300	
10	L-828T	8" In Wall/Ceiling Mount Speaker		Rated power: 6W Line input: 100V Speaker driver size: 8" paper cone	300	




Remarks:

- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.

Horn Speaker

No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	H-13	10W Outdoor All Weather ABS Horn Speaker		Rated power: 10W Line input: 70V/100V ABS material, waterproof IP66	300	
2	H-13S	10W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 10W Line input: 70V/100V ABS material, waterproof IP66	300	
3	H-15	15W Outdoor All Weather Aluminum Horn Speaker		Rated power: 15W Line input: 100V Aluminum, waterproof IP66	300	
4	H-30	30W Outdoor All Weather Aluminum Horn Speaker		Rated power: 30W Line input: 100V Aluminum, waterproof IP66	300	
5	H-50	50W Outdoor All Weather Aluminum Horn Speaker		Rated power: 50W Line input: 100V Aluminum, waterproof IP66	300	
6	H-15S	15W Outdoor All Weather Aluminum Horn Speaker with Power Taps		Rated power: 15W Line input: 70V/100V/8Ω Aluminum, waterproof IP66	300	
7	H-30S	30W Outdoor All Weather Aluminum Horn Speaker with Power Taps		Rated power: 30W Line input: 70V/100V/8Ω Aluminum, waterproof IP66	300	
8	H-50S	50W Outdoor All Weather Aluminum Horn Speaker with Power Taps		Rated power: 50W Line input: 70V/100V/8Ω Aluminum, waterproof IP66	300	
9	H-161HD	Outdoor High Fidelity Waterproof Aluminum Horn Speaker		Rated power: 25W Line input: 70V/100V Aluminum, waterproof IP66	300	
10	H-162HD	Outdoor High Fidelity Waterproof Aluminum Horn Speaker		Rated power: 50W Line input: 70V/100V Aluminum, waterproof IP66	300	
11	H-163HD	Outdoor High Fidelity Waterproof Aluminum Horn Speaker		Rated power: 25W (high impedance) Line input: 70V/100V Aluminum, waterproof IP66	300	
12	H-168HD	50W Outdoor High Fidelity All Weather Horn Speaker		Rated power: 50W Line input: 70V/100V ABS material, waterproof IP66	300	
13	H-3154	15W Outdoor All Weather Horn Speaker		Rated power: 15W Line input: 70V/100V FRP material, waterproof IP66	300	
14	H-3304	30W Outdoor All Weather Horn Speaker		Rated power: 30W Line input: 70V/100V FRP material, waterproof IP66	300	
15	H-3204	40W Explosion Proof Aluminum Horn Speaker		Rated power: 40W Line input: 70V/100V Explosion proof, Aluminum, waterproof IP66	200	
16	H-3305	Big Power Outdoor All Weather Horn Speaker		Rated power: 300W Line input: 70V/100V or 160V FRP material, IP66	30	
17	H-3306	Big Power Outdoor All Weather Horn Speaker		Rated power: 600W Line input: 70V/100V or 160V FRP material, IP66	30	
18	H-3307	Big Power Outdoor All Weather Horn Speaker		Rated power: 1000W Line input: 70V/100V or 160V FRP material, IP66	30	





19	H-34	15W Outdoor All Weather ABS Horn Speaker		Rated power: 15W Line input: 100V ABS material, waterproof IP66	300	
20	H-43	30W Outdoor All Weather ABS Horn Speaker		Rated power: 30W Line input: 100V ABS material, waterproof IP66	300	
21	H-34S	15W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 15W Line input: 70V/100V/8Ω ABS material, waterproof IP66	300	
22	H-43S	30W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 30W Line input: 70V/100V/8Ω ABS material, waterproof IP66	300	
23	H-45	30W Outdoor All Weather ABS Horn Speaker		Rated power: 30W Line input: 70V/100V ABS material, waterproof IP66	300	
24	H-45S	30W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 30W Line input: 70V/100V ABS material, waterproof IP66	300	
25	H-47	80W Outdoor All Weather ABS Horn Speaker		Rated power: 80W Line input: 100V ABS material, waterproof IP66	300	
26	H-48	50W Outdoor All Weather ABS Horn Speaker		Rated power: 50W Line input: 100V/8Ω ABS material, waterproof IP66	300	
27	H-815	15W Outdoor All Weather ABS Horn Speaker		Rated power: 15W Line input: 100V ABS material, waterproof IP66	300	
28	H-830	30W Outdoor All Weather ABS Horn Speaker		Rated power: 30W Line input: 100V ABS material, waterproof IP66	300	
29	H-815S	15W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 15W Line input: 70V/100V/8Ω ABS material, waterproof IP66	300	
30	H-830S	30W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 30W Line input: 70V/100V/8Ω ABS material, waterproof IP66	300	
31	H-A10	10W Outdoor All Weather ABS Horn Speaker		Rated power: 10W Line input: 100V ABS, waterproof IP66	300	
32	H-A20	15W Outdoor All Weather ABS Horn Speaker		Rated power: 15W Line input: 100V ABS, waterproof IP66	300	
33	H-A30	30W Outdoor All Weather ABS Horn Speaker		Rated power: 30W Line input: 100V ABS, waterproof IP66	300	
34	H-A10S	10W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 10W Line input: 70V/100V/8Ω ABS material, waterproof IP66	300	
35	H-A20S	15W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 15W Line input: 70V/100V/8Ω ABS material, waterproof IP66	300	
36	H-A30S	30W Outdoor All Weather ABS Horn Speaker with Power Taps		Rated power: 30W Line input: 70V/100V/8Ω ABS material, waterproof IP66	300	
37	H-RC80	8" 120W Outdoor All Weather Big Power Horn Speaker		Rated power: 120W Line input: 8Ω ABS, waterproof IP66	100	
38	H-RC80T	8" 120W Outdoor All Weather Big Power Horn Speaker		Rated power: 120W Power taps: 7.5/15/30/60/120W/8Ω Line input: 70V/100V/8Ω ABS, waterproof IP66	100	






39	H-RC100	10" 200W Outdoor All Weather Big Power Horn Speaker		Rated power: 200W Line input: 8Ω ABS, waterproof IP66	100	
40	H-RC100T	10" 200W Outdoor All Weather Big Power Horn Speaker		Rated power: 200W Power taps: 12.5/25/50/100/200W/8Ω Line input: 70V/100V/8Ω ABS, waterproof IP66	100	
41	H-RC120T	12" 300W Outdoor All Weather Big Power Horn Speaker		Rated power: 300W Power taps: 18.5/37.5/75/150/300W/8Ω Line input: 70V/100V/8Ω ABS, waterproof IP66	100	
42	HS-1230	12 Inch 300W Outdoor All-Weather Compact Full-Range Two-Way Coaxial Stadium Loudspeaker		Rated power: 300W Line input: 8Ω 12" Bass, 1" treble Aluminum grill ABS, waterproof IP66	100	

Remarks:

- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.

Column Speaker

No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	C-122	2.5" 10W Outdoor Waterproof Aluminum Column Speaker		Rated power: 10W Line input: 70V/100V Speaker driver size: 2.5"	300	
2	C-124	2.5" 20W Outdoor Waterproof Aluminum Column Speaker		Rated power: 20W Line input: 70V/100V Speaker driver size: 2.5"	300	
3	C-126	2.5" 30W Outdoor Waterproof Aluminum Column Speaker		Rated power: 30W Line input: 70V/100V Speaker driver size: 2.5"	300	
4	C-128	2.5" 40W Outdoor Waterproof Aluminum Column Speaker		Rated power: 40W Line input: 70V/100V Speaker driver size: 2.5"	300	
5	C-322	2.5" 10W Outdoor Waterproof Aluminum Column Speaker		Rated power: 10W Line input: 100V Speaker driver size: 2.5"	300	
6	C-324	2.5" 20W Outdoor Waterproof Aluminum Column Speaker		Rated power: 20W Line input: 100V Speaker driver size: 2.5"	300	
7	C-326	2.5" 30W Outdoor Waterproof Aluminum Column Speaker		Rated power: 30W Line input: 100V Speaker driver size: 2.5"	300	
8	C-328	2.5" 40W Outdoor Waterproof Aluminum Column Speaker		Rated power: 40W Line input: 100V Speaker driver size: 2.5"	300	
9	C-411	4" 10W Outdoor Waterproof Aluminum Column Speaker		Rated power: 10W Line input: 100V Speaker driver size: 4"	300	
10	C-412	4" 20W Outdoor Waterproof Aluminum Column Speaker		Rated power: 20W Line input: 100V Speaker driver size: 4"	300	
11	C-413	4" 30W Outdoor Waterproof Aluminum Column Speaker		Rated power: 30W Line input: 100V Speaker driver size: 4"	300	
12	C-414	4" 40W Outdoor Waterproof Aluminum Column Speaker		Rated power: 40W Line input: 100V Speaker driver size: 4"	300	
13	C-425	4" 20W Indoor Wooden Column Speaker		Rated power: 20W Line input: 70V/100V Speaker driver size: 4"	300	
14	C-435	4" 30W Indoor Wooden Column Speaker		Rated power: 30W Line input: 70V/100V Speaker driver size: 4"	300	
15	C-445	4" 40W Indoor Wooden Column Speaker		Rated power: 40W Line input: 70V/100V Speaker driver size: 4"	300	
16	C-510	4" 10W Outdoor Waterproof Aluminum Column Speaker		Rated power: 10W Line input: 100V Speaker driver size: 4"	300	
17	C-520	4" 20W Outdoor Waterproof Aluminum Column Speaker		Rated power: 20W Line input: 100V Speaker driver size: 4"	300	
18	C-530	4" 30W Outdoor Waterproof Aluminum Column Speaker		Rated power: 30W Line input: 100V Speaker driver size: 4"	300	
19	C-540	4" 40W Outdoor Waterproof Aluminum Column Speaker		Rated power: 40W Line input: 100V Speaker driver size: 4"	300	

20	C-710	6" 10W Outdoor Waterproof Aluminum Column Speaker		Rated power: 10W Line input: 100V Speaker driver size: 6"	300	
21	C-720	6" 20W Outdoor Waterproof Aluminum Column Speaker		Rated power: 20W Line input: 100V Speaker driver size: 6"	300	
22	C-730	6" 30W Outdoor Waterproof Aluminum Column Speaker		Rated power: 30W Line input: 100V Speaker driver size: 6"	300	
23	C-740	6" 40W Outdoor Waterproof Aluminum Column Speaker		Rated power: 40W Line input: 100V Speaker driver size: 6"	300	
24	C-750	6" 50W Outdoor Waterproof Aluminum Column Speaker		Rated power: 50W Line input: 100V Speaker driver size: 6"	300	
25	C-760	6" 60W Outdoor Waterproof Aluminum Column Speaker		Rated power: 60W Line input: 100V Speaker driver size: 6"	300	
26	C-810	4" 10W Outdoor Waterproof Aluminum Column Speaker with Tweeter		Rated power: 10W Line input: 100V Speaker driver size: 4"+1.5" Mylar	300	
27	C-820	4" 20W Outdoor Waterproof Aluminum Column Speaker with Tweeter		Rated power: 20W Line input: 100V Speaker driver size: 4"+1.5" Mylar	300	
28	C-830	4" 30W Outdoor Waterproof Aluminum Column Speaker with Tweeter		Rated power: 30W Line input: 100V Speaker driver size: 4"+1.5" Mylar	300	
29	C-840	4" 40W Outdoor Waterproof Aluminum Column Speaker with Tweeter		Rated power: 40W Line input: 100V Speaker driver size: 4"+1.5" Mylar	300	
30	CS-1501	100W Phased Array Column Speaker		Rated power: 100W Acoustic configurable beam LED screen display	50	
31	CS-1502	150W Phased Array Column Speaker		Rated power: 150W Acoustic configurable beam LED screen display	50	
32	CS-M400	80W/8Ω Outdoor Aluminum Waterproof Column Speaker		Rated power: 80W Line input: 8Ω Speaker unit: 4"x4 + 1"x1 All Aluminum	50	
33	CS-M600	120W/8Ω Outdoor Aluminum Waterproof Column Speaker		Rated power: 120W Line input: 8Ω Speaker unit: 4"x6 + 1"x2 All Aluminum	50	
34	CS-M400T	80W/100 Outdoor Aluminum Waterproof Column Speaker		Rated power: 80W Line input: 100V Speaker unit: 4"x4 + 1"x1 All Aluminum	50	
35	CS-M600T	120W/100 Outdoor Aluminum Waterproof Column Speaker		Rated power: 120W Line input: 100V Speaker unit: 4"x6 + 1"x2 All Aluminum	50	

Remarks:

- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.



LY INTERNATIONAL ELECTRONICS CO.,LTD.






Room 1206, Aoyuan Business Building, No. 26 Jinlong Road Nansha District, Guangzhou China.

Skype: lyintlcorp; WhatsApp/WeChat: +86-13710702050

Tel: +86-20-39390663, Fax: +86-20-39390669








E-mail: sales@lyintl.com



Http://www.lyintl.com

Projection Speaker						
No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	P-303	5" 10W Unidirectional Aluminum Projection Speaker		Rated power: 10W 5" paper cone speaker unit Aluminum material Unidirectional	300	
2	P-310	6.5" 20W Unidirectional Aluminum Projection Speaker		Rated power: 20W 6.5" paper cone speaker unit Aluminum material Unidirectional	300	
3	P-305	5" 10W Bidirectional Aluminum Projection Speaker		Rated power: 10W 5" paper cone speaker unit Aluminum material Bidirectional	300	
4	P-311	6.5" 20W Bidirectional Aluminum Projection Speaker		Rated power: 20W 6.5" paper cone speaker unit Aluminum material Bidirectional	300	
5	P-306	5" 10W Unidirectional ABS Projection Speaker		Rated power: 10W 5" paper cone speaker unit ABS material Unidirectional	300	
6	P-323	6.5" 20W Unidirectional ABS Projection Speaker		Rated power: 20W 6.5" paper cone speaker unit ABS material Unidirectional	300	
7	P-307	5" 10W Bidirectional ABS Projection Speaker		Rated power: 10W 5" paper cone speaker driver ABS material Bidirectional	300	
8	P-D30S	5" 30W ABS Unidirectional Projection Speaker		Rated power: 30W 5" paper cone speaker driver ABS material Unidirectional	300	

Remarks:













- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.




Pendent Speaker						
No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	H-301	5" 10W Aluminum Pendant Speaker		Rated power: 10W 5" paper cone speaker unit Aluminum material	300	
2	H-312	6.5" 20W Aluminum Pendant Speaker		Rated power: 20W 6.5" paper cone speaker unit Aluminum material	300	
3	H-308	5" 10W ABS Pendant Speaker		Rated power: 10W 5" paper cone speaker unit ABS material	300	
4	H-325	6.5" 10W ABS Pendant Speaker		Rated power: 20W 6.5" paper cone speaker unit ABS material	300	
5	H-5B	5" 10W HIPS Pendant Speaker		Rated power: 10W 5" paper cone speaker unit HIPS material	200	
6	H-5C	5" 10W HIPS Pendant Speaker		Rated power: 10W 5" paper cone speaker unit HIPS material	200	
7	H-6A	6" 30W ABS Pendant Speaker		Rated power: 30W 6" paper cone speaker unit ABS material	300	
8	H-6AC	6" 2-way 30W ABS Pendant Speaker		Rated power: 30W 6" paper cone speaker unit (2-way) ABS material	300	
9	H-8A	8" 20W ABS Pendant Speaker		Rated power: 20W 8" paper cone speaker unit ABS material	300	
10	HS-3404	4" 20W All Weatherproof Waterproof Pendant Speaker		Rated power: 20W Line input: 70V/100V/8Ω 4" woofer + 0.75" tweeter IP66 All weatherproof	300	
11	HS-3504	5.25" 30W All Weatherproof Waterproof Pendant Speaker		Rated power: 30W Line input: 70V/100V/8Ω 5.25" woofer + 1" tweeter IP66 All weatherproof	300	
12	HS-3604	6.5" 40W All Weatherproof Waterproof Pendant Speaker		Rated power: 40W Line input: 70V/100V/8Ω 6½" woofer + 1" tweeter IP66 All weatherproof	300	

13	HS-5404	4" 20W Pendant Speaker		Rated power: 20W Power taps: 2.5/5/10/20W/0/8Ω Line input: 70V/100V/8Ω 4" woofer + 0.75" silk tweeter	300	
14	HS-5504	5" 30W Pendant Speaker		Rated power: 30W Power taps: 3.75/7.5/15/30W/0/8Ω Line input: 70V/100V/8Ω 5.25" woofer + 1" silk tweeter	300	
15	HS-5604	6.5" 40W Pendant Speaker		Rated power: 40W Power taps: 5/10/20/40W/0/8Ω Line input: 70V/100V/8Ω 6.5" woofer + 1" silk tweeter	300	
16	HS-5804	8" 50W Pendant Speaker		Rated power: 50W Power taps: 6.25/12.5/25/50W/0/8Ω Line input: 70V/100V/8Ω 8" woofer + 1.1" silk tweeter	300	
17	HS-6404	4" 20W Indoor/Outdoor IP66 Waterproof Pendant Speaker		Rated power: 20W Line input: 70V/100V/8Ω 4" woofer + silk tweeter IP66 All weatherproof With optimal bass enhancement radiator	300	
18	HS-6504	5" 30W Indoor/Outdoor IP66 Waterproof Pendant Speaker		Rated power: 30W Line input: 70V/100V/8Ω 5" woofer + silk tweeter IP66 All weatherproof With optimal bass enhancement radiator	300	
19	HS-6604	6.5" 40W Indoor/Outdoor IP66 Waterproof Pendant Speaker		Rated power: 40W Line input: 70V/100V/8Ω 6½" woofer + silk tweeter IP66 All weatherproof With optimal bass enhancement radiator	300	
20	HS-6804	8" 50W Indoor/Outdoor IP66 Waterproof Pendant Speaker		Rated power: 50W Line input: 70V/100V/8Ω 8" woofer + silk tweeter IP66 All weatherproof With optimal bass enhancement radiator	300	

Remarks:












- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.




Garden Speaker						
No.	Model	Product	Image	Short Description	MOQ (pcs)	Remarks
1	G-20	20W Outdoor All Weather Waterproof ABS Garden Speaker		Rated power: 20W Line input: 100V ABS material, waterproof IP44	200	
2	G-21	30W Outdoor All Weather Waterproof ABS Garden Speaker		Rated power: 30W Line input: 100V ABS material, waterproof IP44	200	
3	G-3601	45W Outdoor All Weather Waterproof Aluminum Garden Speaker		Rated power: 45W Line input: 70V/100V Aluminum, waterproof IPX6	100	
4	G-3620	20W 6.5" Outdoor All Weather Waterproof Imitate Mushroom Landscape Speaker		Rated power: 20W Line input: 70V/100V Resin material, waterproof IPX6	100	
5	G-3630	30W Outdoor All Weather Waterproof Imitate Mushroom Landscape Speaker		Rated power: 30W Line input: 70V/100V Resin material, waterproof IPX6	100	
6	G-3640	45W 6.5" Outdoor All Weather Waterproof Imitate Rock Landscape Speaker		Rated power: 45W Line input: 70V/100V Resin material, waterproof IP66	100	
7	G-3641	20W 5" Outdoor All Weather Waterproof Imitate Rock Landscape Speaker		Rated power: 20W Line input: 70V/100V Resin material, waterproof IP66	100	
8	G-3642	20W 6.5" Outdoor All Weather Waterproof Imitate Rock Landscape Speaker		Rated power: 20W Line input: 70V/100V Resin material, waterproof IP66	100	
9	G-3643	40W 6.5" Outdoor All Weather Waterproof Imitate Rock Landscape Speaker		Rated power: 40W Line input: 70V/100V Resin material, waterproof IP66	100	
10	G-3644	60W 8" Outdoor All Weather Waterproof Imitate Rock Landscape Speaker		Rated power: 60W Line input: 70V/100V Resin material, waterproof IP66	100	
11	G-3645	40W 8" Outdoor All Weather Waterproof Imitate Rock Landscape Speaker		Rated power: 40W Line input: 70V/100V Resin material, waterproof IP66	100	
12	G-3647	30W 5.5" Outdoor All Weather Waterproof Imitate Rock Landscape Speaker		Rated power: 30W Line input: 70V/100V Resin material, waterproof IP66	100	
13	G-3660	4.5" 20W Outdoor All Weather Waterproof Landscape Garden Speaker		Rated power: 20W Line input: 100V Plastic material, waterproof IP66	100	

14	PS-3404	4" All Weatherproof Landscape Speaker Ground Stand		Rated power: 20W Line input: 70V/100V/8Ω 4" woofer + 0.75" tweeter IP66 All weatherproof	300	
15	PS-3504	5.25" All Weatherproof Landscape Speaker Ground Stand		Rated power: 30W Line input: 70V/100V/8Ω 5.25" woofer + 1" tweeter IP66 All weatherproof	300	
16	PS-3604	6.5" All Weatherproof Landscape Speaker Ground Stand		Rated power: 40W Line input: 70V/100V/8Ω 6½" woofer + 1" tweeter IP66 All weatherproof	300	
22	WS-4320	3 Inch 20W Outdoor All Weather Resistant Wall Mount Patio Speaker		Rated power: 20W Line input: 70V/100V 3" full range speaker driver IP66 All weatherproof	300	
23	PS-4320	3 Inch 20W Outdoor All Weather Resistant In Ground Spike Stand Landscape Garden Speaker Ground Stand		Rated power: 20W Line input: 70V/100V 3" full range speaker driver IP66 All weatherproof	300	

Remarks:

- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 15 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.

Wireless Speaker						
No.	Model	Product	Image	Short Description	MOQ (pairs)	Remarks
1	WS-301BT	5" 10W 1 Channel Bluetooth Wireless Ceiling Speaker (1 active)		Rated power: 1*10W Line input: 8Ω Speaker driver: 5.25" paper cone With Bluetooth input	30	pc
2	WS-302BT	5" 2*10W Bluetooth Ceiling Speaker (1 active + 1 passive)		Rated power: 2*10W Line input: 8Ω Speaker driver: 5.25" paper cone With Bluetooth input	30	set (1+1)
3	WS-304BT	5" 4*10W Bluetooth Ceiling Speaker (1 active + 3 passive)		Rated power: 4*10W Line input: 8Ω Speaker driver: 5.25" paper cone With Bluetooth input	30	set (1+3)
4	WS-605BT	5" 2CH Bluetooth Active Wireless Coaxial In Ceiling Speaker (1 active + 1 passive)		Rated power: 2*10W Speaker driver: woofer 5"*1 + tweeter 1"*1 Build-in 2 channel digital Class D amplifier With Bluetooth / AUX input	100	set (1+1)
5	WS-606BT	6" 2CH Bluetooth Active Wireless Coaxial In Ceiling Speaker (1 active + 1 passive)		Rated power: 2*30W Speaker driver: woofer 6"*1 + tweeter 1"*1 Build-in 2 channel digital Class D amplifier With Bluetooth / AUX input	100	set (1+1)
6	WS-608BT	8" 2CH Bluetooth Active Wireless Coaxial In Ceiling Speaker (1 active + 1 passive)		Rated power: 2*40W Speaker driver: woofer 8"*1 + tweeter 1"*1 Build-in 2 channel digital Class D amplifier With Bluetooth / AUX input	100	set (1+1)
7	WS-602WF	6" 2*30W WiFi Wireless 2-way Coaxial Ceiling Speaker (1 active + 1 passive)		Rated power: 2*30W Line input: 8Ω Speaker driver: 6" paper + 1" tweeter With Bluetooth / WiFi / AUX input	30	set (1+1)
8	WS-604WF	6" 4*30W WiFi Wireless 2-way Coaxial Ceiling Speaker (1 active + 3 passive)		Rated power: 4*30W Line input: 8Ω Speaker driver: 6" paper + 1" tweeter With Bluetooth / WiFi / AUX input	30	set (1+3)
9	WS-704BT	4" 2 Channel Bluetooth Wireless 2-way Coaxial Active Ceiling Speaker (1 active + 1 passive)		Rated power: 2*10W Speaker driver: 4"*1+1"*1 Product size: 172*172*123 mm Cutting hole: 150 mm Weight: 2KG	30	set (1+1)
10	WS-705BT	5" 2 Channel Bluetooth Wireless 2-way Coaxial Active Ceiling Speaker (1 active + 1 passive)		Rated power: 2*20W Speaker driver: 5"*1+1"*1 Product size: 210*210*152 mm Cutting hole: 185 mm Weight: 2.3KG	30	set (1+1)
11	WS-706BT	6" 2 Channel Bluetooth Wireless 2-way Coaxial Active Ceiling Speaker (1 active + 1 passive)		Rated power: 2*30W Speaker driver: 6"*1+1"*1 Product size: 238*238*180 mm Cutting hole: 215 mm Weight: 2.5KG	30	set (1+1)

12	WS-525BT	5½" 2*30W Bluetooth Wall Mount Speaker		<p>Rated power: 2*30W Line input: 8Ω</p> <p>Speaker driver: 5½" paper +1½" tweeter With RCA and 6.3m Mic input With Bluetooth input Individual volume control</p>	50	set (1+1)
13	WS-525WF	5½" 2*25W Wifi Wireless Wall Mount Speaker		<p>Rated power: 2*25W Line input: 8Ω</p> <p>Speaker driver: 5½" paper +1½" tweeter With RJ45, RCA, 6.3m Mic input Built-in Wifi wireless receiver Individual volume control</p>	100	set (1+1)
14	WS-525GX	5½" 2*30W 2.4G Wireless Wall Mount Speaker		<p>Rated power: 2*30W Line input: 8Ω</p> <p>Speaker driver: 5½" paper +1½" tweeter With RCA and 6.3m Mic input Built-in 2.4G wireless receiver Individual volume control</p>	50	set (1+1)

Remarks:

- 1, Above prices are based on FOB terms for FCL order, EXW terms will be applied for LCL.
- 2, Price validity period is 30 days.
- 3, Product quality warranty period is 1 year.
- 4, OEM is available.