

L-623/L-603 /L-613 specifications

General Specification

Type	L-623	L-603	L-613
Frequency Response	100-15KHZ		
SPL	97dB at 100V 3W	97dB at 100V 3W	99dB at 100V 5W
Sensitivity	93±3DB	93±3DB	93±3DB
Power Handling	6W	6W	10W
Power Taps	3W/6W	3W/6W	5W/10W
Line input	100V		
Hole for mounting	Φ 150mm	Φ 170mm	Φ 205mm
Dimension(D*H)	Φ 175*60mm	Φ 188*76mm	Φ 228*90mm

Physical Specification

Material	ABS(adult white)		
Grille	Powder Coated Iron Mesh (White ral 9016)		
Component	5"	6"	8"
Finished Colour	White		
Unit Weight	0.5Kg	0.7Kg	1Kg
Gross Weight	9kg/12pcs	12kg/12pcs	15kg/12pcs
Packing Dimension(cm)	41*38*21	49*41*23	61*49*27

Speaker Specification

Voice Coil Size	PSV14.28* Φ0.1*2T	PSV20.4 Φ0.12*2T	PSV20.4 Φ0.12*2T
DC Impedance	7.2 Ω		
Former	Paper		
Magnet	Ferrite(105g) Φ 55* Φ 24*10(Y30)	Ferrite(153g) Φ 70*32*10(Y25)	Ferrite(270g) Φ 80*32*12(Y25)
Basket	ABS		
Cone Material	Paper		
Spider	Cloth		
Dust cap	Paper Cup		
Net Weight	360g	520g	680g

