

PP-822URBT



PLUG & PLAY DISCUSSION

THAT FEELS AT HOME EVERYWHERE

PP-822URBT

All in one design for easy carrying and portable use. SMT technology and SMD electronic components used in building this amplifier, so the quality is very stable and last long. Low power consumption for long time operation with integrated circuitry.

This speaker system works on both AC and DC, you can also use the built in 1.2AH rechargeable battery, or with car cigarette lighter power for DC 12V. (The power cord for car is not included.)



FEATURES:

- ◆ AUX input for connecting to MD/CD etc.
- ◆ AUX output, 8 ohms speaker output.
- ◆ USB play function in MP3 format.
- ◆ With Bluetooth play function.
- ◆ Tone control.
- ◆ Wired/wireless microphone.
- ◆ Digital echo control.
- ◆ Quartz stabilizer for carrier frequency transmission to avoid interference.
- ◆ UHF band 0~99 different possible frequencies from 700 MHz to 900 MHz
- ◆ 12V common battery 8.4V rechargeable battery
- ◆ 3 styles of microphones are good for different purposes. You can use the handheld mic, headset mic and Lavalier alternatively. Uni-directional Lavalier microphone with high sensitivity for clearly voice transmission and receiving.
- ◆ Low voltage circuit protection for the built-in rechargeable battery to avoid the damage of the rechargeable battery in case of incorrect operation.

PP-822URBT

SPECIFICATIONS

Model	PP-822URBT
Output power	50W (max)
Input	1xAUX, 1xΦ6.5 wired MIC
Output	1xAUX, 1x8Ω speaker out
Build-in	<ul style="list-style-type: none">- Digital MP3, USB card Player- 1x Aux Input Jack- Bluetooth player- 1x 6.35mm dynamic microphone input jack- 1x 3.5mm condenser microphone input jack- Volume Control; Echo Control; Mic Volume Control; Music Volume Control- 1x Aux output with 10 meter audio cable, 1x 8Ω speaker output
Frequency channel	Dual wireless channel (Handheld/Lapel/Micro Headset Mic)
Frequency range	UHF 700-900MHz
Sensitivity	10dB/*V
S/N	>60dB
T.H.D.	<1%
Speaker size	1x6.5" full range speaker (4Ω)
Wireless range	80m Max
Power supply	AC 110V/220V~240V 1A External: DC 12V-1A Built-in DC 12V-1.2AH rechargeable battery or build-in DC 12V-2.2AH Li-ion battery
Dimension (mm)	180(W) x 110(D) x 300(H)
Gross weight (Kg)	2.7 Maximum
Operating temperature	-25°C~50°C

LY International Electronics Co., Ltd

1206 Aoyuan Jinsha Plaza Building, No. 26 Jinlong Road Nansha District, Guangzhou, China

Phone: (+86) 20 3939 0663

Fax: (+86) 20 3939 0669

E-mail: sales@lyintl.com