

F-8062/F-8063/F-8064 4"/5"/6.5" On Wall Mount Speaker

Product ID: F-8062/F-8063/F-8064



Short Description

Rated power: 20W / 30W / 40W

Line input: 70V/100V/8?

Speaker driver: 4"/5"/6.5" + 1" tweeter

Description

ABS on wall mount cabinet speaker with PP or paper woofer speaker driver and 1" silk tweeter, 70V/100V/8? input.

Speaker driver size:

F-8062: 4" PP woofer + 1" silker tweeter, power taps: 4/8/15/20W

F-8063: 5" PP woofer + 1" silk tweeter, power taps: 5/8/15/30W

F-8064: 6.5" Paper woofer + 1" silk tweeter, power taps: 5/10/20/40W

Specification

Model	F-8062	F-8063	F-8064
Rated power	20W	30W	40W
Power taps (70V)	2/4/8/15W	2.5/5/8/15W	2.5/5/10/20W
Powder taps	4/8/15/20W	5/8/15/30W	5/10/20/40W

(100V)			
Line input	70V/100/8?		
Sensitivity (1m,1W)	90±2dB	90±2dB	91±2dB
Max SPL	103±2dB	105±2dB	107±2dB
Frequency response	90-20KHz	80-20KHz	65-20KHz
Woofer speaker driver	4"x1 PP	5"x1 PP	6"x1 Paper
Tweeter speaker driver	1"x1 Silk		
Product dimension (mm)	176x170x255	194x185x280	215x203x310
Frame material	ABS		
Grille material	Powder coated Aluminum mesh		
Color	White / Black		
Product net weight	2.64Kg	3.2Kg	4.6Kg
Gross weight	-	-	-
Packing dimension	-	-	-

Product Gallery



