

L-455T/L-555T/L-655T/L-855T 4"/5"/6"/8" Slim Edge Ceiling Speaker

Product ID: L-455T/L-555T/L-655T/L-855T



Short Description

Rated power: 20W/20W/30W/40W
Line input: 100V
Woofer speaker driver: 4" or 5" or 6" or 8" PP cone, ½" tweeter
Bezel-less magnetic grille

Description

Slim Edge ABS Ceiling Speaker with 4"/5"/6"/8" PP cone woofer speaker driver and cloth edge, 100V input.

- L-455: rated power 20W, power taps: 5/10/20W
- L-555: rated power 20W, power taps: 7.5/15/30W
- L-655: rated power 30W, power taps: 5/10/20W
- L-855: rated power 40W, power taps: 10/20/40W

With bezel-less magnetic grille for easy and secure attachment.

Specification

Model	L-455T	L-555T	L-655T	L-855T
-------	--------	--------	--------	--------

Rated power	20W	20W	30W	40W
Power taps	5/10/20W	5/10/20W	7.5/15/30W	10/20/40W
Line input	100V			
Sensitivity (1m,1W)	88±3dB	88±3dB	88±3dB	90±3dB
Frequency response	100-20KHz	100-20KHz	90-20KHz	50-20KHz
Woofer speaker driver	4" PP	5" PP	6" PP	8" PP
Tweeter speaker driver	1/2" Mylar			
Product dimension (mm)	180x80	203x85	232x90	257x95
Hole for mounting (mm)	160	180	200	245
Frame material	ABS			
Grille material	Powder coated Iron mesh			
Color	White (RAL9016)			
Product net weight (Kg)	1.2	1.3	1.8	1.8
Gross weight (Kg)	-	-	-	-
Packing dimension (cm)	-	-	-	-

Product Gallery

