

PB-200P/PB-300P/PB-600P/PB-1000P 60W-350W Single Zone Mixer Amplifier

Product ID:
PB-200P/PB-300P/PB-600P/PB-1000P



Short Description

Rated power: 60W/120W/250W/350W

3 MIC input, 2 AUX inputs, 1 AUX output for link

Description

Classical mixer amplifier comes with 3 microphone input and 2 aux input, mic 1 is provided with priority and muting function.

Bass and treble individual control and master volume control are provided.

Complete protection includes short circuit and thermal protection, current limiter and overloading.

- ? 3 MIC inputs, MIC 1 with priority muting function
- ? 2 AUX inputs & 1 output line for additional mixer or amplifier
- ? Individual volume control for each MIC and line input
- ? Bass and treble volume control separately
- ? 5 unit LED level display
- ? Output short-circuit protection and alarm

Specification

Model	PB-200P	PB-300P	PB-600P	PB-1000P
Output power	60W	120W	250W	350W
Speaker output	balanced 4?, 100V, 70V			
Output regulation	±3dB (from off-load to full load)			
AUX output	600? more than 0.775V (0dBm)			
Input	MIC 1, 2, 3/600?, 3.5mV unbalanced			
	AUX 1, 2/10K?, 300mV unbalanced			
Frequency response	80Hz-16KHz (±3dB)			
Distortion	Less than 0.8% at 1KHz, 1/3 rated power			
S/N	MIC 1, 2, 3: 70dB			
	AUX 1, 2: 75dB			
Tone	Bass: ±10dB at 100Hz			
	Treble: ±10dB at 10KHz			
Protection	AC fuse; DC voltage; overload; short-circuit			
Muting function	MIC 1 overrides other signal inputs with 0~ -3dB attenuation			
Power requirements	AC220-240V/50-60Hz			
Power consumption	120W	250W	500W	650W
Net weight (Kg)	8.5	9	13	13.4
Gross weight (Kg)	10.3	10.8	14.8	15.2
Product dimension (mm)	420x88x338			
Packing dimension (mm)	520×430×195			

Product Gallery

