LY International Electronics Co., Ltd - Room 1206 Aoyuan Jinsha Plaza Business Building, No. 26 Jinlong Road Nansha District, Guangzhou China, 511458
Phone: +86-20-39390663 - Email: sales@lyintl.com

PB-480Z/PB-650Z 4 Zone Digital Mixer Amplifier with Remote Paging

Product ID: PB-480Z/PB-650Z



Short Description

Rated output power: 480W; 650W
3 MIC input, 2 RCA line input, 1x6.3mm AUX input

Description

? 3 MIC input, MIC1 with muting function
? 2 RCA line input, 1 6.3mm AUX input
? 3 Input channel volume individual control & tone control
? Master, basee and treble volume control
? 4 Zone speaker 100V output
? RJ45 jack for zone selectable remote mic (EM-4)
? LED selector and indicators
? Short circuit protection & alarm

Specification

Model	PB-480Z	PB-650Z

Rated output power (RMS)	480W	650W
Input Sensitivity/Impedance	MIC 1,2,3: -50dB / 20K? (balanced) Line 2,3: 0dB / 20K? (unbalanced)	
Output leve / Impedance	100V (21?)	100V (16?)
Frequencey response	80Hz-18KHz (-3dB)	
T.H.D.	<0.1% at 1KHz, 1/3 rated output power	
S/N ratio	>81dB	
Tone control	100Hz, 10KHz, ±10dB	
Protection	AC fuse, DC voltage, Overload, Short circuit	
Muting function	MIC1 overrides other input signals at 0~30dB	
Power supply	AC220~230V/50~60Hz	
Product dimension (WxDxH)	420x320x88mm	
Net Weight (Kg)	5.5	5.7

Product Gallery

