

# L-VCM24A/EN Honeywell 24W 6.5" 2-Way Fireproof Metal Ceiling Speaker EN54-24

**Product ID:** L-VCM24A/EN (582480)



## Short Description

Rated power: 24W

Speaker unit: 2-way 6.5"

Comply with EN54-24 standard

## Description

- ? Comply with EN54-24 requirements
- ? With fire dome to protect wire connection
- ? Fireproof plastic wire joint and ceramic terminal
- ? High-class steel and form by stamping
- ? Aluminum grille, stainless and durable
- ? Clip type flush mount design for easy installation
- ? Equipped with steel hanging line, double ensure

## Specification

Model		L-VCM24A/EN (582480)
Rated/Max power		24W/36W
Power taps	100V	24W / 12W / 6W / 3W / 4?
	70V	12W / 6W / 3W / 1.5W / 4?
Line input voltage		100V/70V
Rated impedance		0.42k? / 0.83k? / 1.67k? / 3.33k? / 4?
Sensitivity at rated power /1W	100 Hz-10k Hz, 1m	103dB/91d
	100 Hz-10k Hz, 4m	91dB/79dB
Frequency response (-10dB)		120-20KHz
Dispersion angle (1kHz/-6dB)		165°
Connection		Ceramic Terminal
Dimension (mm)		?226x129
Hole for mounting (mm)		?196
Speaker driver unit		full range 6.5"
Material		Iron
Grill color		White (RAL 9003)
Dome color		Red (RAL 3000)
Weight (Kg)		2.25

## Product Gallery

