

L-VWM06A/EN Honeywell 4" Fireproof Metal Cabinet Speaker EN54-24

Product ID: L-VWM06A/EN (582470)



Short Description

Rated power: 6W

Speaker unit: 4"

Comply with EN54-24 standard

Description

- ? Comply with EN54-24 requirements
- ? With fire dome to protect wire connection
- ? Fireproof plastic wire joint and ceramic terminal
- ? High-class steel and form by stamping
- ? Aluminum grille, stainless and durable
- ? Clip type flush mount design for easy installation
- ? Equipped with steel hanging line, double ensure

Specification

Model		L-VWM06A/EN (582470)
Rated/Max power		6W/9W
Power taps	100V	6/3/1.5/0.75W
	70V	3/1.5/0.75/0.375W
Line input voltage		100V/70V
Rated impedance		1.7k Ω /3.3k Ω /6.7k Ω /13k Ω
Sensitivity at rated power /1W	100 Hz-10k Hz, 1m	98dB/91d
	100 Hz-10k Hz, 4m	86dB/79dB
Frequency response (-10dB)		300-15KHz
Dispersion angle (1kHz/-6dB)		175 $^{\circ}$ (H), 174 $^{\circ}$ (V)
Connection		Ceramic Terminal
Dimension (mm)		170x170x63
Hole for mounting (mm)		-
Speaker driver unit		full range 4"
Material		Steel
Grill color		White (RAL 9003)
Dome color		-
Weight (Kg)		1.56

Product Gallery



