

X-NPMI Honeywell Configurable Network Paging Console

Product ID: X-NPMI



Short Description

Provide paging, monitoring
Built-in monitor loudspeaker
Touch screen operation

Description

X-NPMI is a key module in X-618 Digital Public Address and Voice Alarm System, configurable Network Paging Console with X-DCS2000/EN and other X-618 components via Ethernet. It provides paging, monitoring, full duplex communication, touch screen operation and other configurable functions.

- ? 4.3-inch color LCD touch screen, can display system states, broadcast to 1 zone or a group of zones, and achieve various control via "touch"
- ? Intuitive and simple user interface
- ? Extension, maximum 20 X-NPMI per system, number of function button can be expanded via software without needs of additional keyboard module
- ? Detachable gooseneck microphone
- ? Built-in monitor loudspeaker, can achieve functions such as zone monitoring and two-

way intercom among X-NPMI/ENs

? Digital audio processing to avoid sound distortion during transmissions

? Lightweight and innovative ID patent pending design, enable desktop flush mount installation

Specification

Parameter	Value
Power supply voltage	DC 12V / 24V
Rated power	5W
MIC Frequency response	80Hz~16KHz
SNR	>85dB
THD	<0.05%
Microphone input	-44dB±2dB
Monitoring loudspeaker	2W / 8?
LCD size	4.3"
Sampling rate	44.1KHz, 16Bit
Operating temperature	-10??+ 55?
Storage temperature	-40??+ 70?
Relative Humidity	<95%, without condensation
Dimension (W×H×D)	210 × 55 × 110 mm
Package dimension (W×H×D)	403 × 133 × 268 mm
Net weight	0.78Kg
Gross weight	1.6Kg

Product Gallery

