

# M-6182II IP Network Public Address System Control Center

**Product ID: M-6182II**



## **Short Description**

Support upto 1000 zones  
Network zone paging available  
Audio input channels extensible  
LAN installation, no need extra wiring

## **Description**

The M-6182 series network PA system is an integrated and intelligent PA system, based on internet and built in modules and layers, digital transmission and realized by Lan, transmission distance can be more than 10 kilometers. Configuration of the system can take advantage of the existing LAN system, time & cost is saving. The network system make it possible for interaction due to its combination with LAN system, while the traditional PA system unable to reach.

Multiple terminals can be connected to this network PA system control center, such like the terminal player, on-demand terminal, paging terminal, one-touch emergency alarm terminal. Besides, the system control center combined audio player, paging, pre-amplifier, timer, equalizer, and powerful audio matrix function, etc.

This network system can be applied to different occasions, like the airport, port,

university, school, large gathering site (e.g. Expo), stadium, industrial park, park, railway and highway, etc.

- ? 17" large color LCD display, touch screen and touch-pad
- ? Support upto 1000 zones, any zone, any time and any audio source play programmable
- ? Zone paging available from the main center and external paging terminal
- ? Zonal monitor, able to monitor the play mode and volume of the terminal
- ? Audio input channels extensible by network paging terminals
- ? Build-in CD player and mass storage for user choosing sound source
- ? Timer function, timing points can be programmed directly on the main unit or on PC and then downloaded into the main center
- ? One key touch-ready for all zone alarm or manual alarm
- ? LAN installation, no need extra wiring

## Specification

Item	Parameter
Model	M-6182II
Display Screen	17.3 inch LED screen
Operation control	Touch screen/pad control
S/N ratio	Line: >70dB MIC: >60dB
T.H.D	<0.5% at 1KHz
System audio input level	Line: 300mV±20mV MIC: 50mV±2mV
System audio output level	0dB
Power output method	Fixed resistance output 4-16Ω
Non-distortion output Power	10W
Power supply capacity	Singel channel current: 2A
Work Environment	Ambient temperature: 5-35°C; Relative Humidity: 75%; Pressure: 86-106kpa
Power consumption	AC 220~240V/50-60Hz/150W
Dimension (mm)	483x445x308
Net weight (Kg)	24.50
Gross weight (Kg)	33.70

## Product Gallery

