

M-6310 2x15W IP Network Terminal Player

Product ID: M-6310



Short Description

Build-in 2x15W digital amplifier

1 AUX input, 1 MIC input, 1 AUX output, 1 EMC output

Support offline local source playing

Description

M-6310 IP network terminal player is a network full digital signal processor based on TCP/IP protocol. With dual network interface design, it can be connect to anywhere at network reaches. Under intelligent control of the system center, this terminal serves to output the long distance audio data flow.

Built in USB port and SD slot for local program playing. With 1 AUX input for connect with other audio source equipment; 1 AUX audio output for connection with other amplifiers for power extension; 1 MIC input for local Paging.

- ? Dual Network interface design, able to work across network segments
- ? Able to connect to anywhere at network reaches
- ? Built in USB port and SD slot for local program playing
- ? Support up to 48kHz sampling frequency, and 16bit digital audio code stream decoding
- ? Built in 2x15w with low power consumption setting
- ? Able to play the background music, emergency broadcast, warning signal from system center

? 1 AUX input, 1 AUX output, 2 MIC input, 1 EMC output

Specification

Model		M-6310
AUX in	Input sensitivity	350V
	Frequency response	26Hz-18kHz
	Distortion	?0.5%
	SNL	?75 dB
AUX out	Rated output	1000mV
	Frequency response	25Hz-20kHz
	Distortion	?0.3%
	SNL	?75 dB
Distortion	Distortion	3.5mV
	Frequency response	30Hz-18kHz
	Distortion	?0.5%
	SNL	?65 dB
USB/SD/NET/MP3 Display	Frequency response	25Hz-20kHz
	Distortion	?0.5%
	SNL	?70dB
Capacity of SD card supported		32GB
Capacity of U disk supported		32GB
Power supply		AC180-250V/50Hz-60Hz
Display screen		Digital Screen
Net weight (Kg)		1.2
Dimension?L×W×H mm?		132×140×50

Product Gallery

