

M-6806/M-6812/M-6825/M-6835/M-6865

Network Player Amplifier

Product ID:

M-6806/M-6812/M-6825/M-6835/M-6865



Short Description

Rated power: 60W/120W/250W/350W/650W

100V constant voltage output

1 AUX and 1 MIC input, 1 AUX output

Description

This series network based power amplifier is a fully networking digital analog-digital signal processor supporting 100/10Mbps self-adaptation TCP/IP network transmission protocol;

With the design of double network backup, it is allowed to access to any switch simultaneously.

Audio data stream from the host can be output and played through the machine;

Built-in MP3 player with USB and SD card port, so it can play the local MP3 program from this machine without playing the internet audio signal;

1 AUX input for connection other audio source equipments (e.g. DVD, radio);

1 AUX output for connection other power amplifiers;

1 MIC input used for local paging.

? Equipped with MP3 player, USB and SD port

? Rated output power: 60W, 120W, 250W, 350W

- ? 100V constant voltage output
- ? 1 AUX audio input and 1 MIC input, 1 AUX output
- ? 100V local emergency input
- ? High-grade aluminum-alloy drawn panel
- ? Can be used in any place accessible to the network

Specification

Model		M-6806/M-6812/M-6825/ M-6835/M-6865
AUX Input	Input sensitivity	1000mV
	Frequency response	20Hz-20kHz
	Distortion	≤0.1%
	S/N ratio	≥75 dB
MIC Input	Input sensitivity	10mV
	Frequency response	20Hz-20kHz
	Distortion	≤0.5%
	S/N ratio	≥70 dB
USB/SD/NET Playing MP3	Frequency response	20Hz-20kHz
	Distortion	≤0.5%
	S/N ratio	≥75 dB
AUX Output	Rated output	1000mV
	Frequency response	20Hz-20kHz
	Distortion	≤0.1%
	S/N ratio	≥75 dB
100V constant voltage output	Rated output	60W/120W/250W/350W/6 50W
	Frequency response	100Hz-15kHz
	Distortion	≤1%
	S/N ratio	≥70 dB
Capacity supporting SD card		32GB
Capacity supporting U-disk		32GB
Display screen		Digital screen
Over-current, overheat, over-voltage protection		Satisfied
Power supply		AC220V/50Hz-60Hz
Machine dimension (L×W×H mm)		483×410×88
Packing dimension (L×W×H mm)		520×485×145
Weight (Kg)		7.0 / 7.3 / 7.39 / 8.92 / 9.92