LY International Electronics Co., Ltd - Room 1206 Aoyuan Jinsha Plaza Business Building, No. 26 Jinlong Road Nansha District, Guangzhou China, 511458
Phone: +86-20-39390663 - Email: sales@lyintl.com

M-6311 15W IP Network Ceiling Speaker

Product ID: M-6311



Short Description

Built-in 2x15W digital amplifier

Built-in 4? 15W Hi-Fi speakers
1 AUX & 1 MIC input, 1 AUX output

Description

Support BGM, emergency paging and siren alarm from the system center host machine;
Local MP3 program can be played when the network audio stream signal is not played;
1 AUX audio input for connection with other audio source devices (such as DVD);
1 AUX audio output for connection with other power amplifiers;
1 MIC input for achieving local paging.

? 100/10Mbps, TCP/IP network transmission protocol adaptive
? Built-in 2x15W high efficiency digital amplifier with low power-consuming
? Built-in 15W 4? Hi-Fi speakers with high output sensitivity
? 1 AUX audio input, 1 microphone input, 1 AUX audio output
? 100V local emergency input, easy to connect with the local fire alarming system
? Output volume and display status can be controlled by system host

Specification

Model	M-6311

AUX Input	Input sensitivity	1000mV
	Frequency response	20Hz-20kHz
	Distortion	?0.5%
	S/N	?75dB
MIC Input	Output sensitivity	10mV
	Frequency response	20Hz-20kHz
	Distortion	?0.5%
	S/N	?65dB
AUX Output	Rated output	1000mV
	Frequency response	20Hz-20kHz
	Distortion	?0.3%
	S/N	?75dB
Amplifier Output	Power	15W/4?
	Frequency response	20Hz-20kHz
	Distortion	?0.5%
	S/N	?75dB
Built-in Speaker	Max SPL	?100dB
	Power	15W/4?
	Frequency response	20Hz-20kHz
	Distortion	?0.5%
	S/N	?75dB
USB/SD/Net/MP3	Frequency respones	20Hz-20kHz
	Distortion	?0.5%
	S/N	?70dB
SD card storage		32GB
U disk storage		32GB
Power Supply		180-250V/50-60Hz
Product weight (Kg)		1.5
Dimension (LxWxH mm)		250x175x255